SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

7PNCSS1USBBC-W

Hartland CFX Polished Nickel 1 gang	13A Single Pole Switched Socket with 1 US	B Outlets 1x2.1A Bright Chrome/White	
Item Image	Wiring	Dimensions	
		Hemilton HARTLAND CFX SSTUSBX1 USB Charger + Switched Socket	
		86.0 - 5.0 - 21.2 - 21.	
Primary Range	Hartland CFX		
Insert Type	1 gang 13A Single Pole Switched Socket with 1 USB Outlet 1x2.1A		
Plate Finish	Hartland CFX Polished Nickel		
Insert Colour	Bright Chrome/White		
EAN13 Barcode	5017504089238		
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Switched Poles	Single		
Current Rating	13 Amp, USB = 2.1A		
Voltage	180/250V AC		
Maximum Load	13 Amp, USB = 2.1A		
Mains Frequency	50/60Hz		
IP Rating	IP2XD		
Contact Gap Minimum	3mm		
Terminal Capacity 1	3 x 2.5mm2		
Terminal Capacity 2	3 x 4mm2		
Terminal Capacity 3	2 x 6mm2 Multi-Strand		
Earth Terminal Capacity 1	3 x 2.5mm2		
Earth Terminal Capacity 2	3 x 4mm2		
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand	2 x 6mm2 Multi-strand	
Product Class 1	Must be earthed		
Ambient Operating Temperature	-15°C to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS1363, BS5733, EN60950-1		
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 12:42 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











