

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

7RBCR222BL-B

Item Image	Wiring Wiring The state of th	Dimensions Hemilton HARTLAND CFX R222 2 Way Rocker			
			Primary Range	Hartland CFX	
			Insert Type	2 gang 20AX 2 Way Rocker	
Plate Finish	Hartland CFX Richmond Bronze				
Insert Colour	Black/Black				
EAN13 Barcode	5017504014629				
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm				
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips				
Minimum Wall Box Depth	25mm				
Switched Poles	Single				
Current Rating	20AX				
Voltage	220/250V AC				
Maximum Load	20 Amp inductive				
Mains Frequency	50Hz				
IP Rating	IP2XD				
Contact Gap Minimum	3mm				
Terminal Capacity 1	5 x 1mm2				
Terminal Capacity 2	4 x 1.5mm2				
Terminal Capacity 3	2 x 2.5mm2				
Terminal Capacity 4	2 x 4mm2 Multi-strand				
Terminal Capacity 5	1 x 6mm2				
Earth Terminal Capacity 1	6 x 1mm2				
Earth Terminal Capacity 2	5 x 1.5mm2				
Earth Terminal Capacity 3	3 x 2.5mm2				
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand				
Earth Terminal Capacity 5	1 x 6mm2				
Product Class 1	Must be earthed				
Ambient Operating Temperature	-5° to +40°C				
Recommended Location	Internal Use Only				
Maximum Installation Altitude	2000m				
Standard/Approval	BS EN 60669-1				
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 12:42 PN E&Ol			

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio