Hamilton

making connections beautifully

SL

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio | | |
|--|--|---|
| 7RC1X40BL | | |
| Hartland CFX Colours Pillar Box Red 1x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Black | | |
| Item Image | Wiring | Dimensions |
| | Dimmer Wing b Martin b M | ELECTION CFX COLOURS 1x40 Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer |
| Primary Range | Hartland CFX Colours | |
| Insert Type | 1 gang 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer | |
| Plate Finish | Hartland CFX Colours Pillar Box Red | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017504007287 | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Push | |
| Minimum Wall Box Depth | 35mm | |
| Wattage | 400W | |
| Switched Poles | Single 4.66 Ame | |
| Current Rating | 1.66 Amp | |
| Voltage | 220/250V AC | |
| Maximum Load | 400W resistive Min Load 50Hz | |
| Mains Frequency IP Rating | SUHZ IP2XD | |
| Contact Gap Minimum | N/A | |
| • | 2 x 1mm2 | |
| Terminal Capacity 1 Terminal Capacity 2 | 2 x 1.5mm2 | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 4 x 1.5mm2 3 x 2.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 1 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 4 Earth Terminal Capacity 5 | 1 x 4mm2 Multi-Strand | |
| Product Class 1 | Face plate must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-2-1 | |
| Additional Notes | Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. | |
| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 15 October 2018 10:21 AM E&OE |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84 | | |