Hamilto

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 7RC1XLEDITB100BL Hartland CFX Colours Pillar Box Red 1g 100W LED 2 Way Push On/Off Rotary Dimmer Black Item Image Wiring Dimensions Hemilton HARTLAND CFX COLOURS 1XI EDITR LEDITB100 2 Way Dimmer 86.0 Primary Range Hartland CFX Colours Insert Type 1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Hartland CFX Colours Pillar Box Red Insert Colour Black EAN13 Barcode 5017504080181 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm **Fixing Hole Centres** Box Fixing = 60.3mm Grid Fixing = CFX Push Minimum Wall Box Depth 35mm Wattage 5-100W (10 LED Lamps MAX) Switched Poles Single Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) 50Hz Mains Frequency IP Rating IP2XD **Terminal Capacity 1** 2X1mm² **Terminal Capacity 2** 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm² Product Class 1 Face plate muct be earthed -5°C to +40°C Ambient Operating Temperature **Recommended Location** Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Trailing Edge & Leading Edge Dimmer Additional Notes Patents and Trademarks CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme Therefore, we reserve the right to alter designs correct at the time of going to press. and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 15 October 2018 10:21 AM the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE process and are not binding. of certain finishes R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimble T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.bossilte...!! & ECA

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84 hamilton-litestat.com www.hamilton-litestat.com

SL