




7RC2J12B

Hartland CFX Colours Pillar Box Red 2 gang RJ12 Outlet - Unshielded Black

Item Image	Wiring	Dimensions																																				
	 <table border="1" data-bbox="808 646 966 730"> <thead> <tr> <th>Pin</th> <th>Color</th> <th>Wire Color</th> <th>Socket Color</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>GREEN / White</td> <td>BLUE</td> <td>GREEN</td> </tr> <tr> <td>2</td> <td>ORANGE / White</td> <td>YELLOW</td> <td>ORANGE</td> </tr> <tr> <td>3</td> <td>WHITE / Blue</td> <td>RED</td> <td>WHITE</td> </tr> <tr> <td>4</td> <td>BLUE / White</td> <td>BLACK</td> <td>BLUE</td> </tr> <tr> <td>5</td> <td>WHITE / Orange</td> <td>BLACK</td> <td>WHITE</td> </tr> <tr> <td>6</td> <td>RED / Green</td> <td>WHITE</td> <td>RED</td> </tr> <tr> <td>7</td> <td>RED / Green</td> <td>WHITE</td> <td>RED</td> </tr> <tr> <td>8</td> <td>RED / Green</td> <td>WHITE</td> <td>RED</td> </tr> </tbody> </table>	Pin	Color	Wire Color	Socket Color	1	GREEN / White	BLUE	GREEN	2	ORANGE / White	YELLOW	ORANGE	3	WHITE / Blue	RED	WHITE	4	BLUE / White	BLACK	BLUE	5	WHITE / Orange	BLACK	WHITE	6	RED / Green	WHITE	RED	7	RED / Green	WHITE	RED	8	RED / Green	WHITE	RED	 <p>Hamilton HARTLAND CFX COLOURS 2J12 2 gang RJ12 Outlet Unshielded 6 wire</p>
Pin	Color	Wire Color	Socket Color																																			
1	GREEN / White	BLUE	GREEN																																			
2	ORANGE / White	YELLOW	ORANGE																																			
3	WHITE / Blue	RED	WHITE																																			
4	BLUE / White	BLACK	BLUE																																			
5	WHITE / Orange	BLACK	WHITE																																			
6	RED / Green	WHITE	RED																																			
7	RED / Green	WHITE	RED																																			
8	RED / Green	WHITE	RED																																			
Primary Range	Hartland CFX Colours																																					
Insert Type	2 gang RJ12 Outlet - Unshielded																																					
Plate Finish	Hartland CFX Colours Pillar Box Red																																					
Insert Colour	Black																																					
EAN13 Barcode	5017504007324																																					
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm																																					
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Push																																					
Minimum Wall Box Depth	35mm																																					
Switched Poles	N/A																																					
IP Rating	IP2XD																																					
Contact Gap Minimum	N/A																																					
Earth Terminal Capacity 1	5 x 1mm ²																																					
Earth Terminal Capacity 2	4 x 1.5mm ²																																					
Earth Terminal Capacity 3	3 x 2.5mm ²																																					
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand																																					
Earth Terminal Capacity 5	1 x 6mm ²																																					
Product Class 1	Must be earthed (ref BS7671 415.2.1)																																					
Ambient Operating Temperature	-5° to +40°C																																					
Recommended Location	Internal Use Only																																					
Maximum Installation Altitude	2000m																																					
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)																																					
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667																																					
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																																				
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 10:21 AM E&OE																																				

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84

