


## 7RCC11BL-B

### Hartland CFX Colours Pillar Box Red 1 gang 10A (6AX) Card Switch On/Off with Blue LED Locator Black/Black

Item Image	Wiring	Dimensions
	<p>Wiring diagrams showing connections for Live, Neutral, and Load. The diagrams are for a Hamilton LITESTAT 10A(6AX) 230V~50Hz u BS EN 60669-2-3:2006 MDSG-CARDKEYSWT.</p> <p>or</p> <p>Wiring diagrams showing connections for Live, Neutral, and Earth. The diagrams are for a Hamilton LITESTAT 10A(6AX) 230V~50Hz u BS EN 60669-2-3:2006 MDSG-CARDKEYSWT.</p>	<p>Dimensions: 86.0mm x 86.0mm x 5.0mm (depth). The diagram shows a square face with a central keyhole and a side view showing the depth.</p> <p><b>Hamilton</b> HARTLAND CFX COLOURS C11 Card Switch</p>

Primary Range	Hartland CFX Colours
Insert Type	1 gang 10A (6AX) Card Switch On/Off with Blue LED Locator
Plate Finish	Hartland CFX Colours Pillar Box Red
Insert Colour	Black/Black
EAN13 Barcode	5017504007607
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Push
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	10A (6AX)
Voltage	220/250V AC
Maximum Load	10 Amp (6 Amp inductive)
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	3 x 1mm <sup>2</sup>
Terminal Capacity 2	2 x 1.5mm <sup>2</sup>
Terminal Capacity 3	1 x 2.5mm <sup>2</sup>
Earth Terminal Capacity 1	5 x 1mm <sup>2</sup>
Earth Terminal Capacity 2	4 x 1.5mm <sup>2</sup>
Earth Terminal Capacity 3	3 x 2.5mm <sup>2</sup>
Earth Terminal Capacity 4	1 x 4mm <sup>2</sup> Multi-strand
Earth Terminal Capacity 5	1 x 6mm <sup>2</sup>
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS EN 60669-2-3
Additional Notes	Adjustable Time Delay 10 seconds - 5 minutes. Suitable for 44mm and 54mm width Hotel Key Cards
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667

<p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p>	<p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>	<p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p>
<p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>	<p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p>	<p>Correct as at 15 October 2018 10:21 AM E&amp;OE</p>