SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

7WPCSATNW Hartland CFX Primed White 1 gang Non-Isolated Satellite White Item Image Wiring **Dimensions** Hamilton SATN Isolated Satellite Single Screen Clamp 0 Hartland CFX Primary Range Insert Type 1 gang Non-Isolated Satellite Plate Finish Hartland CFX Primed White Insert Colour White EAN13 Barcode 5017504015787 Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles N/A IP Rating IP2XD Contact Gap Minimum N/A Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand

European standard and the product information is correct at the time of going to press. Illustrations and diagrams are reproduced within

All products listed conform to current British or

the limitations of reproduction and printing

process and are not binding.

All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.

Hartland CFX is a Registered Design under Reference Nos.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.

It is the policy of the company to improve products as part of our development programme Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 16 October 2018 12:43 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Earth Terminal Capacity 5

Recommended Location Maximum Installation Altitude

Patents and Trademarks

Ambient Operating Temperature

Product Class 1

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

1 x 6mm2

-5° to +40°C

2000m

Internal Use Only

Must be earthed (ref BS7671 415.2.1)

R21 = 3023446 SS2 = 3023445

CFX is a Registered Trade Mark No 2398667









