Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 7WPCSS2USBULTWH-W Hartland CFX Primed White 2 gang 13A Double Pole Switched Socket with 2 USB Ultra Outlets 2x2.4A White/White Item Image Wiring Dimensions × Primary Range Hartland CFX Insert Type 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) Plate Finish Hartland CFX Primed White Insert Colour White/White EAN13 Barcode 5017504090326 Commodity Code 85363010 Luckins TSI 405689136 **Dimensions** (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double 13 Amp, USB = 2.4A Current Rating 180/250V AC Voltage Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz IP Rating IP2XD Contact Gap Minimum 3mm **Terminal Capacity 1** 3 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 **Terminal Capacity 3** 2 x 6mm2 Multi-Strand Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Product Class 1 Must be earthed -15°C to +40°C Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363 + BS 5733 + EN 60950-1 CFX is a Registered Trade Mark No 2398667 Patents and Trademarks Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 03 July 2019 07:23 AM the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE process and are not binding of certain finishes R Hamilton & Co Ltd. Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in Trimble SECA T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 E: info@hamilton-litestat.com www.hamilton-litestat.com

SL