
Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 802XLEDITB100 Sheer Gloss White 2g 100W LED 2 Way Push On/Off Rotary Dimmer Gloss White					
			Sheer Gloss while 2g 100W LED 2 way Push On/On Rolary Diminer Gloss while		
			Item Image	Wiring	Dimensions
		Hamilton			
		SHEER 2XLEDITB			
		LEDITB100 2 Way Dimmer			
•					
Primary Range	Sheer				
Insert Type	2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer				
Plate Finish	Sheer Box Gloss White				
Insert Colour	Gloss White				
EAN13 Barcode	5017504080396				
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm				
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A				
Minimum Wall Box Depth	35mm				
Wattage	5-70W Per Gang				
Switched Poles	Single				
Current Rating	0.3A Per Gang				
Voltage	230V-240V				
Maximum Load	5-70W Per Gang				
Mains Frequency	50Hz				
IP Rating	IP2XD 2X1mm ²				
Terminal Capacity 1					
Terminal Capacity 2	2X1.5mm ²				
Earth Terminal Capacity 1	5X1mm ²				
Earth Terminal Capacity 2	4X1.5mm ²				
Earth Terminal Capacity 3	3X2.5mm ²				
Earth Terminal Capacity 4	1X4mm ² Multi-Strand				
Earth Terminal Capacity 5	1X6mm ²				
Product Class 1	Face plate muct be earthed				
Ambient Operating Temperature	-5°C to +40°C				
Recommended Location	Internal Use Only 2000m				
Maximum Installation Altitude	BS EN 60669-2-1				
Standard/Approval Additional Notes					
Additional Notes Patents and Trademarks	Trailing Edge & Leading Edge Dimmer Sheer is a Registered Trade Mark No. 2296586				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 09:56 AM E&OE			
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro. T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Off E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in R	ad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84	Listed in Strimble LUCKINS Relector DISSPILS Selector CER No. FM1128			



SL