SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

804XLEDITB100 Sheer Gloss White 4g 100W LED 2 Way Push On/Off Rotary Dimmer Gloss White Item Image Wiring **Dimensions** Hamilton 4XLEDITB Primary Range Sheer Insert Type 4 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Sheer Box Gloss White Insert Colour Gloss White EAN13 Barcode 5017504080419 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm²

European standard and the product information is correct at the time of going to press. Illustrations and diagrams are reproduced within the limitations of reproduction and printing

process and are not binding.

All products listed conform to current British or

All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of It is the policy of the company to improve products as part of our development programme Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 17 October 2018 09:56 AM

E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com hamilton-litestat.com www.hamilton-litestat.com

Earth Terminal Capacity 2

Earth Terminal Capacity 3

Earth Terminal Capacity 4

Earth Terminal Capacity 5

Ambient Operating Temperature Recommended Location

Maximum Installation Altitude

Patents and Trademarks

Product Class 1

Standard/Approval

Additional Notes

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84

4X1.5mm²

3X2.5mm²

1X6mm²

2000m

-5°C to +40°C

Internal Use Only

BS EN 60669-2-1

1X4mm² Multi-Strand

Face plate muct be earthed

Trailing Edge & Leading Edge Dimmer

Sheer is a Registered Trade Mark No. 2296586









