




80CJ12W

Sheer CFX Gloss White 1 gang RJ12 Outlet - Unshielded White

Item Image	Wiring	Dimensions																				
	 <table border="1" data-bbox="808 646 966 730"> <thead> <tr> <th>RIGHT RJ11 / 12 Wiring colour codes:</th> <th>LEFT RJ11 / 12 Wiring colour codes:</th> </tr> </thead> <tbody> <tr> <td>NO. 1 NOT USED</td> <td>NO. 6 NOT USED</td> </tr> <tr> <td>2 GREEN / White</td> <td>5 BLUE</td> </tr> <tr> <td>3 ORANGE / White</td> <td>4 YELLOW</td> </tr> <tr> <td>4 WHITE / Blue</td> <td>3 GREEN</td> </tr> <tr> <td>5 BLUE / White</td> <td>2 RED</td> </tr> <tr> <td>6 WHITE / Orange</td> <td>1 BLACK</td> </tr> <tr> <td>NO. 7 NOT USED</td> <td>NO. 8 NOT USED</td> </tr> <tr> <td>NO. 9 NOT USED</td> <td>NO. 10 NOT USED</td> </tr> <tr> <td>NO. 11 NOT USED</td> <td>NO. 12 NOT USED</td> </tr> </tbody> </table>	RIGHT RJ11 / 12 Wiring colour codes:	LEFT RJ11 / 12 Wiring colour codes:	NO. 1 NOT USED	NO. 6 NOT USED	2 GREEN / White	5 BLUE	3 ORANGE / White	4 YELLOW	4 WHITE / Blue	3 GREEN	5 BLUE / White	2 RED	6 WHITE / Orange	1 BLACK	NO. 7 NOT USED	NO. 8 NOT USED	NO. 9 NOT USED	NO. 10 NOT USED	NO. 11 NOT USED	NO. 12 NOT USED	
RIGHT RJ11 / 12 Wiring colour codes:	LEFT RJ11 / 12 Wiring colour codes:																					
NO. 1 NOT USED	NO. 6 NOT USED																					
2 GREEN / White	5 BLUE																					
3 ORANGE / White	4 YELLOW																					
4 WHITE / Blue	3 GREEN																					
5 BLUE / White	2 RED																					
6 WHITE / Orange	1 BLACK																					
NO. 7 NOT USED	NO. 8 NOT USED																					
NO. 9 NOT USED	NO. 10 NOT USED																					
NO. 11 NOT USED	NO. 12 NOT USED																					
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.																					
Insert Type	1 gang RJ12 Outlet - Unshielded																					
Plate Finish	Sheer CFX Gloss White																					
Insert Colour	White																					
EAN13 Barcode	5017504024819																					
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket																					
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips																					
Minimum Wall Box Depth	35mm																					
Switched Poles	N/A																					
IP Rating	IP2XD																					
Contact Gap Minimum	N/A																					
Earth Terminal Capacity 1	5 x 1mm ²																					
Earth Terminal Capacity 2	4 x 1.5mm ²																					
Earth Terminal Capacity 3	3 x 2.5mm ²																					
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand																					
Earth Terminal Capacity 5	1 x 6mm ²																					
Product Class 1	Must be earthed (ref BS7671 415.2.1)																					
Ambient Operating Temperature	-5° to +40°C																					
Recommended Location	Internal Use Only																					
Maximum Installation Altitude	2000m																					
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)																					
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755																					
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																				
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:39 AM E&OE																				

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84

