## Hamilton

## making connections beautifully

	Wiring Accessories • Circuit Protection • Sn	nar t Egnung Control & Multi-room Audio
	<u>80CUS2W</u>	
Sheer C	FX Gloss White 1 gang 2A Unswitched Sock	ket White
Item Image	Wiring	Dimensions
•		
		Hemilton
		US2 Unswitched Socket
		86.0
		86.0
	Neutral	
rimary Range	Sheer CEX - Designed to fit Folded Metal Wall Box Enclosure	s that comply with BS4662-2006
nsert Type	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006. 1 gang 2A Unswitched Socket	
late Finish	Sheer CFX Gloss White	
nsert Colour	White	
AN13 Barcode	5017504025137	
imensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket	
xing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
linimum Wall Box Depth	35mm	
witched Poles	None	
urrent Rating	2 Amp	
oltage	220/250V AC	
laximum Load	2 Amp	
lains Frequency	50Hz	
P Rating	IP2XD	
ontact Gap Minimum	None	
erminal Capacity 1	5 x 1mm2	
erminal Capacity 2	4 x 1.5mm2	
erminal Capacity 3	2 x 2.5mm2	
erminal Capacity 4	1 x 4mm2	
arth Terminal Capacity 1 arth Terminal Capacity 2	5 x 1mm2 4 x 1.5mm2	
arth Terminal Capacity 2	4 x 1.5mm2 2 x 2.5mm2	
arth Terminal Capacity 3	1 x 4mm2	
roduct Class 1	Must be earthed	
mbient Operating Temperature	-5° to +40°C	
ecommended Location	Internal Use Only	
laximum Installation Altitude	2000m	
tandard/Approval	BS 546	
dditional Notes	Shuttered: Yes	
atents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:39 E&
t Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Rc : +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Or info@hamilton-litestat.com www.hamilton-litestat.com Registered in	ad, Brislington, Bristol, BS4 5NZ ffice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in STrimble product selector DSSPlus CER hs. http://www.met.