SL

# making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


## 80SPNWH-W

Sheer Gloss White 1 gang 13A Double Pole Fused Spur and Neon White/White


## Item Image



## Wiring



### Dimensions



|                                                                                                                                                 | Live                                                                                                  |                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                                                                 |                                                                                                       | <del> </del>                                                                                                                                                                     |
| Primary Range                                                                                                                                   | Sheer                                                                                                 |                                                                                                                                                                                  |
| Insert Type                                                                                                                                     | 1 gang 13A Double Pole Fused Spur + Neon                                                              |                                                                                                                                                                                  |
| Plate Finish                                                                                                                                    | Sheer Box Gloss White                                                                                 |                                                                                                                                                                                  |
| Insert Colour                                                                                                                                   | White/White                                                                                           |                                                                                                                                                                                  |
| EAN13 Barcode                                                                                                                                   | 5017503320929                                                                                         |                                                                                                                                                                                  |
| Dimensions (Nominal)                                                                                                                            | Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm                                                  |                                                                                                                                                                                  |
| Fixing Hole Centres                                                                                                                             | Box Fixing = 60.3mm Grid Fixing = N/A                                                                 |                                                                                                                                                                                  |
| Minimum Wall Box Depth                                                                                                                          | 35mm                                                                                                  |                                                                                                                                                                                  |
| Switched Poles                                                                                                                                  | Double                                                                                                |                                                                                                                                                                                  |
| Current Rating                                                                                                                                  | 13 Amp                                                                                                |                                                                                                                                                                                  |
| Voltage                                                                                                                                         | 220/250V AC                                                                                           |                                                                                                                                                                                  |
| Maximum Load                                                                                                                                    | 13 Amp                                                                                                |                                                                                                                                                                                  |
| Mains Frequency                                                                                                                                 | 50Hz                                                                                                  |                                                                                                                                                                                  |
| IP Rating                                                                                                                                       | IP2XD                                                                                                 |                                                                                                                                                                                  |
| Contact Gap Minimum                                                                                                                             | 3mm                                                                                                   |                                                                                                                                                                                  |
| Terminal Capacity 1                                                                                                                             | 3 x 2.5mm2                                                                                            |                                                                                                                                                                                  |
| Terminal Capacity 2                                                                                                                             | 2 x 4mm2 Multi Strand                                                                                 |                                                                                                                                                                                  |
| Terminal Capacity 3                                                                                                                             | 1 x 6mm2                                                                                              |                                                                                                                                                                                  |
| Earth Terminal Capacity 1                                                                                                                       | 6 x 1mm2                                                                                              |                                                                                                                                                                                  |
| Earth Terminal Capacity 2                                                                                                                       | 5 x 1.5mm2                                                                                            |                                                                                                                                                                                  |
| Earth Terminal Capacity 3                                                                                                                       | 3 x 2.5mm2                                                                                            |                                                                                                                                                                                  |
| Earth Terminal Capacity 4                                                                                                                       | 2 x 4mm2 Multi-strand                                                                                 |                                                                                                                                                                                  |
| Earth Terminal Capacity 5                                                                                                                       | 1 x 6mm2                                                                                              |                                                                                                                                                                                  |
| Product Class 1                                                                                                                                 | Must be earthed                                                                                       |                                                                                                                                                                                  |
| Ambient Operating Temperature                                                                                                                   | -5° to +40°C                                                                                          |                                                                                                                                                                                  |
| Recommended Location                                                                                                                            | Internal Use Only                                                                                     |                                                                                                                                                                                  |
| Maximum Installation Altitude                                                                                                                   | 2000m                                                                                                 |                                                                                                                                                                                  |
| Standard/Approval                                                                                                                               | BS 1363-4                                                                                             |                                                                                                                                                                                  |
| Patents and Trademarks                                                                                                                          | Sheer is a Registered Trade Mark No. 2296586                                                          |                                                                                                                                                                                  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within                                                                                                | Due to manufacturing processes we cannot                                                              | Correct as at 17 October 2018 09:56 Al                                                                                                                                           |

guarantee an exact colour match and shadings of

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

the limitations of reproduction and printing

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84













E&OE