Hamilton

making connections beautifully

Correct as at 17 October 2018 09:57 AM

Listed in STrimble

LUCKINS

8€EC

E&OE

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

811X2V Sheer Polished Brass 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Polished Brass Item Image Wiring Dimensions Hamilton SHEER 1X2V ading Edge Push On-Off Rotary Way Switching Dimmer 60.3 e Primary Range Sheer Insert Type 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Plate Finish Sheer Box Polished Brass Insert Colour Polished Brass EAN13 Barcode 5017503039111 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 200VA (low voltage) Switched Poles Single Current Rating 0.8 Amp 220/250V AC Voltage Maximum Load 200VA (low voltage) Min Load 25VA 50Hz Mains Frequency IP Rating IP2XD Contact Gap Minimum None **Terminal Capacity 1** 2 x 1mm2 **Terminal Capacity 2** 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When Additional Notes dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE: It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme Therefore, we reserve the right to alter designs and dimensions without prior notice. correct at the time of going to press.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

process and are not binding. of certain finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio