## Hamilton

## making connections beautifully

SL

	<u>81C1X60</u>	
Sheer CFX Polished Brass 1 gang 600	W Resistive Leading Edge Push On-Off Rotary 2	2 Way Switching Dimmer Polished Brass
Item Image	Wiring	Dimensions
	Dirromer Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Winning Win	HEIRICIAN Subscription Resistive Leading Edge Push On-Off Rotars 2 Way Switching Dimmer
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.	
nsert Type	1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer	
late Finish	Sheer CFX Polished Brass	
nsert Colour	Polished Brass	
AN13 Barcode	5017504019457	
imensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket	
ixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
linimum Wall Box Depth	35mm	
/attage	600W	
witched Poles	Single	
current Rating		
5	2.5 Amp 220/250V AC	
oltage		
laximum Load	600W resistive Min Load 100W	
lains Frequency	50Hz	
P Rating	IP2XD	
contact Gap Minimum	N/A	
erminal Capacity 1	2 x 1mm2	
erminal Capacity 2	2 x 1.5mm2	
arth Terminal Capacity 1	5 x 1mm2	
arth Terminal Capacity 2	4 x 1.5mm2	
arth Terminal Capacity 3	3 x 2.5mm2	
arth Terminal Capacity 4	1 x 4mm2 Multi-strand	
arth Terminal Capacity 5	1 x 6mm2	
roduct Class 1	Face plate must be earthed	
mbient Operating Temperature	-5° to +40°C	
ecommended Location	Internal Use Only	
aximum Installation Altitude	2000m	
tandard/Approval	BS EN 60669-2-1	
dditional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.	
atents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:40 A E&C

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio