




81CJ45W

Sheer CFX Polished Brass 1 gang RJ45 CAT 5E Outlet - Unshielded White

Item Image	Wiring	Dimensions																																
	 <p>RJ45 CAT5e and CAT6 Wiring Colour Codes</p> <table border="1" data-bbox="795 567 958 672"> <thead> <tr> <th>Pin</th> <th>EIA Wiring Schedule</th> <th>Colour Codes</th> <th>ISDN Colour</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>WHITE / Green</td> <td>WHITE / Orange</td> <td>ORANGE</td> </tr> <tr> <td>2</td> <td>GREEN / White</td> <td>WHITE / Green</td> <td>GREEN</td> </tr> <tr> <td>3</td> <td>WHITE / Orange</td> <td>BLUE / White</td> <td>BLUE</td> </tr> <tr> <td>4</td> <td>BLUE / White</td> <td>WHITE / Blue</td> <td>WHITE</td> </tr> <tr> <td>5</td> <td>ORANGE / White</td> <td>WHITE / Orange</td> <td>BROWN</td> </tr> <tr> <td>6</td> <td>WHITE / Brown</td> <td>WHITE / Brown</td> <td>BROWN</td> </tr> <tr> <td>7</td> <td>BROWN / White</td> <td>BROWN / White</td> <td>BROWN</td> </tr> </tbody> </table> <p>Please always check with the colour coding found on the product.</p>	Pin	EIA Wiring Schedule	Colour Codes	ISDN Colour	1	WHITE / Green	WHITE / Orange	ORANGE	2	GREEN / White	WHITE / Green	GREEN	3	WHITE / Orange	BLUE / White	BLUE	4	BLUE / White	WHITE / Blue	WHITE	5	ORANGE / White	WHITE / Orange	BROWN	6	WHITE / Brown	WHITE / Brown	BROWN	7	BROWN / White	BROWN / White	BROWN	 <p>Hamilton® SHEER CFX J45 1 gang RJ45 -CAT 5E Outlet Unshielded 8 wire</p>
Pin	EIA Wiring Schedule	Colour Codes	ISDN Colour																															
1	WHITE / Green	WHITE / Orange	ORANGE																															
2	GREEN / White	WHITE / Green	GREEN																															
3	WHITE / Orange	BLUE / White	BLUE																															
4	BLUE / White	WHITE / Blue	WHITE																															
5	ORANGE / White	WHITE / Orange	BROWN																															
6	WHITE / Brown	WHITE / Brown	BROWN																															
7	BROWN / White	BROWN / White	BROWN																															
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.																																	
Insert Type	1 gang RJ45 CAT 5E Outlet - Unshielded																																	
Plate Finish	Sheer CFX Polished Brass																																	
Insert Colour	White																																	
EAN13 Barcode	5017504010577																																	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket																																	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips																																	
Minimum Wall Box Depth	35mm																																	
Switched Poles	N/A																																	
IP Rating	IP2XD																																	
Contact Gap Minimum	N/A																																	
Earth Terminal Capacity 1	5 x 1mm ²																																	
Earth Terminal Capacity 2	4 x 1.5mm ²																																	
Earth Terminal Capacity 3	3 x 2.5mm ²																																	
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand																																	
Earth Terminal Capacity 5	1 x 6mm ²																																	
Product Class 1	Must be earthed (ref BS7671 415.2.1)																																	
Ambient Operating Temperature	-5° to +40°C																																	
Recommended Location	Internal Use Only																																	
Maximum Installation Altitude	2000m																																	
EuroFix Additional Notes	Can be used in both EIA 568A and EIA 568B wiring schedules																																	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755																																	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																																
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at 17 October 2018 10:40 AM E&OE																																

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM11238