


## 81CSS2USBULTPB-B

Sheer CFX Polished Brass 2 gang 13A Double Pole Switched Socket with 2 USB Ultra Outlets 2x2.4A Polished Brass/Black

| Item Image  | Wiring   | Dimensions  |
|---|--|---|
|    |  |   |
| Primary Range   | Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.   |   |
| Insert Type   | 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total)  |   |
| Plate Finish  | Sheer CFX Polished Brass   |   |
| Insert Colour   | Polished Brass/Black   |   |
| EAN13 Barcode   | 5017504090357  |   |
| Commodity Code  | 85363010   |   |
| Luckins TSI   | 405689165  |   |
| Dimensions (Nominal)  | Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket   |   |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = CFX Clips   |   |
| Minimum Wall Box Depth  | 35mm   |   |
| Switched Poles  | Double   |   |
| Current Rating  | 13 Amp, USB = 2.4A   |   |
| Voltage   | 180/250V AC  |   |
| Maximum Load  | 13 Amp, USB = 2.4A   |   |
| Mains Frequency   | 50/60Hz  |   |
| IP Rating   | IP2XD  |   |
| Contact Gap Minimum   | 3mm  |   |
| Terminal Capacity 1   | 3 x 2.5mm <sup>2</sup>   |   |
| Terminal Capacity 2   | 3 x 4mm <sup>2</sup>   |   |
| Terminal Capacity 3   | 2 x 6mm <sup>2</sup> Multi-Strand  |   |
| Earth Terminal Capacity 1   | 3 x 2.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 2   | 3 x 4mm <sup>2</sup>   |   |
| Earth Terminal Capacity 3   | 2 x 6mm <sup>2</sup> Multi-strand  |   |
| Product Class 1   | Must be earthed  |   |
| Ambient Operating Temperature   | -15°C to +40°C   |   |
| Recommended Location  | Internal Use Only  |   |
| Maximum Installation Altitude   | 2000m  |   |
| Standard/Approval   | BS 1363 + BS 5733 + EN 60950-1   |   |
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586<br>Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755 |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 03 July 2019 07:23 AM E&OE  |