Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio
	81CTPBL-B	
Sheer CFX	Polished Brass 1 gang 10A Triple Pole Rocke	er Black/Black
Item Image	Wiring	Dimensions
	$ \begin{array}{c c} & & & & \\ & & & & \\ & & & & \\ & & & &$	Hemilton
		TP Triple Pole Rocker
		86.0
		F.
		86.0 P
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosure	es that comply with BS4662-2006.
Insert Type	1 gang 10A Triple Pole Rocker	
Plate Finish	Sheer CFX Polished Brass	
Insert Colour EAN13 Barcode	Black/Black 5017504011505	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	25mm	
Switched Poles	Triple	
Current Rating	10A	
Voltage	220/250V AC	
Maximum Load	10 Amp resistive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1 Terminal Capacity 2	5 x 1mm2 4 x 1.5mm2	
Terminal Capacity 2	1 x 2.5mm2	
Terminal Capacity 4	1 x 4mm2 Multi-strand	
Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m BS EN 60669-1	
Standard/Approval	BS EN 60669-1 CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586	
Patents and Trademarks	Sheer CFX is a Registered Trade Mark No 2398667 Trade Mark No. 229686 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:40 A E&O
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered	Noad, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB n London No. 941624 VAT Registration No. 222 6607 84	Listed in Trimbe LUCKINS rector DSSPUS CRI. Ko. FM11238

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio