SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 81R21BL-B Sheer Polished Brass 1 gang 10AX 2 Way Rocker Black/Black Item Image Wiring **Dimensions** Hamilton Primary Range Sheer Insert Type 1 gang 10AX 2 Way Rocker Plate Finish Sheer Box Polished Brass Insert Colour Black/Black EAN13 Barcode 5017503031214 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single **Current Rating** 10AX 220/250V AC Voltage 10 Amp inductive Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 **Terminal Capacity 3** 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2

Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Patents and Trademarks

Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or

3 x 2.5mm2

1 x 6mm2

Must be earthed

-5° to +40°C Internal Use Only

1 x 4mm2 Multi-strand

European standard and the product information is correct at the time of going to press.

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing process and are not binding.

All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of

of certain finishes.

Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 17 October 2018 09:57 AM

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Earth Terminal Capacity 3

Earth Terminal Capacity 4

Earth Terminal Capacity 5

Recommended Location

Ambient Operating Temperature

Product Class 1

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84







It is the policy of the company to improve products

as part of our development programme



