Hamilton

making connections beautifully

| Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio | | | |
|--|---|--|--|
| <u>821XTSSB-W</u> | | | |
| Sheer Satin Brass 1 gang Multi-Way Touch Slave Controller Satin Brass/White | | | |
| | | | |
| Item Image | Wiring | Dimensions | |
| | | Hamilton | |
| | Multi- Way Wiring using Slave module(s) | SHEER 1XTS | |
| | | Multi-WayTouch Slave Controller | |
| | | | |
| Primary Range | Sheer | | |
| Insert Type | 1 gang Multi-Way Touch Slave Controller | | |
| Plate Finish | Sheer GRID-IT Satin Brass | | |
| Insert Colour | Satin Brass/White | | |
| EAN13 Barcode | 5028690040422 | | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm | | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = 49.2mm | | |
| Minimum Wall Box Depth | 35mm | | |
| Wattage | The same as Touch Master or Ceiling Dimmer | | |
| Switched Poles | N/A | | |
| Current Rating | The same as Touch Master or Ceiling Dimmer | | |
| Voltage | 220/250V AC | | |
| Maximum Load | The same as Touch Master | | |
| Mains Frequency | 50Hz | | |
| IP Rating | IP2XD | | |
| Contact Gap Minimum | N/A | | |
| Terminal Capacity 1 | 2 x 1mm2 | | |
| Terminal Capacity 2 | 2 x 1.5mm2 | | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | | |
| Product Class 1 | Face plate must be earthed | | |
| Ambient Operating Temperature | -5° to +40°C | | |
| Recommended Location | Internal Use Only | | |
| Maximum Installation Altitude | 2000m | | |
| Standard/Approval | BS EN 60669-2-1 | | |
| Additional Notes | Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers | | |
| Patents and Trademarks | Sheer is a Registered Trade Mark No. 2296586 | | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 09:57 AM E&OE | |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 | | | |

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio