SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## 824XTSSB-W

Sheer Satin Brass 4 gang Multi-Way Touch Slave Controller Satin Brass/White Item Image Wiring **Dimensions** Hamilton 4XTS
Multi-WayTouch Slave Controller Multi- Way Wiring using Slave module(s) Primary Range Sheer Insert Type 4 gang Multi-Way Touch Slave Controller Plate Finish Sheer GRID-IT Satin Brass Insert Colour Satin Brass/White EAN13 Barcode 5028690040453 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = 106.5mm Minimum Wall Box Depth 35mm Wattage The same as Touch Master or Ceiling Dimmer Switched Poles N/A Current Rating The same as Touch Master or Ceiling Dimmer 220/250V AC Voltage Maximum Load The same as Touch Master 50Hz Mains Frequency IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C **Ambient Operating Temperature** Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be Additional Notes used with Touch Master Dimmers Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme Therefore, we reserve the right to alter designs and dimensions without prior notice. correct at the time of going to press. Correct as at 17 October 2018 09:58 AM Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot guarantee an exact colour match and shadings of the limitations of reproduction and printing of certain finishes

process and are not binding. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio