SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## 82C2XLEDITB100

Sheer CFX Satin Brass 2g 100W LED 2 Way Push On/Off Rotary Dimmer Satin Brass Item Image Wiring **Dimensions** Hamilton 2XLEDITB LEDITB100 2 Way Dimme Primary Range Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006. Insert Type 2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Sheer CFX Satin Brass Insert Colour Satin Brass EAN13 Barcode 5017504080594 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang 50Hz Mains Frequency IP Rating IP2XD Terminal Capacity 1 2X1mm<sup>2</sup> Terminal Capacity 2 2X1.5mm<sup>2</sup> Earth Terminal Capacity 1 5X1mm<sup>2</sup> Earth Terminal Capacity 2 4X1.5mm<sup>2</sup> Earth Terminal Capacity 3 3X2.5mm<sup>2</sup> Earth Terminal Capacity 4 1X4mm<sup>2</sup> Multi-Strand Earth Terminal Capacity 5 1X6mm<sup>2</sup> Product Class 1 Face plate muct be earthed -5°C to +40°C **Ambient Operating Temperature** Internal Use Only Recommended Location Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Patents and Trademarks Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001: 2015 Quality Management System. as part of our development programme correct at the time of going to press Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 17 October 2018 10:40 AM guarantee an exact colour match and shadings of the limitations of reproduction and printing E&OE process and are not binding. of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











