




## 82C3XTSSB-W

### Sheer CFX Satin Brass 3 gang Multi-Way Touch Slave Controller Satin Brass/White

| Item Image  | Wiring   | Dimensions  |
|---|--|---|
|    |   |    |
| Primary Range   | Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.   |   |
| Insert Type   | 3 gang Multi-Way Touch Slave Controller  |   |
| Plate Finish  | Sheer CFX Satin Brass  |   |
| Insert Colour   | Satin Brass/White  |   |
| EAN13 Barcode   | 5017504025564  |   |
| Dimensions (Nominal)  | Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket   |   |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = CFX Clips   |   |
| Minimum Wall Box Depth  | 35mm   |   |
| Wattage   | The same as Touch Master or Ceiling Dimmer   |   |
| Switched Poles  | N/A  |   |
| Current Rating  | The same as Touch Master or Ceiling Dimmer   |   |
| Voltage   | 220/250V AC  |   |
| Maximum Load  | The same as Touch Master   |   |
| Mains Frequency   | 50Hz   |   |
| IP Rating   | IP2XD  |   |
| Contact Gap Minimum   | N/A  |   |
| Terminal Capacity 1   | 2 x 1mm <sup>2</sup>   |   |
| Terminal Capacity 2   | 2 x 1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand  |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>   |   |
| Product Class 1   | Face plate must be earthed   |   |
| Ambient Operating Temperature   | -5° to +40°C   |   |
| Recommended Location  | Internal Use Only  |   |
| Maximum Installation Altitude   | 2000m  |   |
| Standard/Approval   | BS EN 60669-2-1  |   |
| Additional Notes  | Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers |   |
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586<br>Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755   |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 17 October 2018 10:40 AM E&OE   |

# Hamilton<sup>®</sup>

making connections beautifully

SL

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio