




## 82C45NW

### Sheer CFX Satin Brass 1 gang 45A Double Pole Rocker and Neon Red/White

| Item Image  | Wiring   | Dimensions  |
|---|--|---|
|    |   |    |
| Primary Range   | Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.   |   |
| Insert Type   | 1 gang 45A Double Pole Red Rocker + Neon   |   |
| Plate Finish  | Sheer CFX Satin Brass  |   |
| Insert Colour   | Red/White  |   |
| EAN13 Barcode   | 5017504024710  |   |
| Dimensions (Nominal)  | Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket  |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |   |
| Minimum Wall Box Depth  | 35mm   |   |
| Switched Poles  | Double   |   |
| Current Rating  | 45 Amp   |   |
| Voltage   | 220/250V AC  |   |
| Maximum Load  | 45 Amp   |   |
| Mains Frequency   | 50Hz   |   |
| IP Rating   | IP2XD  |   |
| Contact Gap Minimum   | 3mm  |   |
| Terminal Capacity 1   | 3 x 6mm <sup>2</sup>   |   |
| Terminal Capacity 2   | 2 x 10mm <sup>2</sup>  |   |
| Terminal Capacity 3   | 1 x 16mm <sup>2</sup>  |   |
| Earth Terminal Capacity 1   | 3 x 6mm <sup>2</sup>   |   |
| Earth Terminal Capacity 2   | 2 x 10mm <sup>2</sup>  |   |
| Earth Terminal Capacity 3   | 1 x 16mm <sup>2</sup>  |   |
| Product Class 1   | Must be earthed  |   |
| Ambient Operating Temperature   | -5° to +40°C   |   |
| Recommended Location  | Internal Use Only  |   |
| Maximum Installation Altitude   | 2000m  |   |
| Standard/Approval   | BS EN 60669-1  |   |
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586<br>Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755 |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 17 October 2018 10:40 AM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
T: +44 (0)1747 860088 F: +44 (0)1179 710414  
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **Trimble LUCKINS**



CERT. No. FM11238