




82CJ12W

Sheer CFX Satin Brass 1 gang RJ12 Outlet - Unshielded White

Item Image	Wiring	Dimensions																		
	 <table border="1" data-bbox="795 630 958 735"> <thead> <tr> <th>RIGHT RJ11/12 Wiring color codes:</th> <th>LEFT RJ11/12 Wiring color codes:</th> </tr> </thead> <tbody> <tr> <td>1. NOT USED</td> <td>NOT USED</td> </tr> <tr> <td>2. GREEN / White</td> <td>BLUE</td> </tr> <tr> <td>3. ORANGE / White</td> <td>YELLOW</td> </tr> <tr> <td>4. WHITE / Blue</td> <td>GREEN</td> </tr> <tr> <td>5. BLUE / White</td> <td>RED</td> </tr> <tr> <td>6. WHITE / Orange</td> <td>BLACK</td> </tr> <tr> <td>7. NOT USED</td> <td>NOT USED</td> </tr> <tr> <td>8. NOT USED</td> <td>NOT USED</td> </tr> </tbody> </table>	RIGHT RJ11/12 Wiring color codes:	LEFT RJ11/12 Wiring color codes:	1. NOT USED	NOT USED	2. GREEN / White	BLUE	3. ORANGE / White	YELLOW	4. WHITE / Blue	GREEN	5. BLUE / White	RED	6. WHITE / Orange	BLACK	7. NOT USED	NOT USED	8. NOT USED	NOT USED	 <p>Hamilton® SHEER CFX J12 1 gang RJ12 Outlet Unshielded 6 wire</p>
RIGHT RJ11/12 Wiring color codes:	LEFT RJ11/12 Wiring color codes:																			
1. NOT USED	NOT USED																			
2. GREEN / White	BLUE																			
3. ORANGE / White	YELLOW																			
4. WHITE / Blue	GREEN																			
5. BLUE / White	RED																			
6. WHITE / Orange	BLACK																			
7. NOT USED	NOT USED																			
8. NOT USED	NOT USED																			
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.																			
Insert Type	1 gang RJ12 Outlet - Unshielded																			
Plate Finish	Sheer CFX Satin Brass																			
Insert Colour	White																			
EAN13 Barcode	5017504020552																			
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket																			
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips																			
Minimum Wall Box Depth	35mm																			
Switched Poles	N/A																			
IP Rating	IP2XD																			
Contact Gap Minimum	N/A																			
Earth Terminal Capacity 1	5 x 1mm ²																			
Earth Terminal Capacity 2	4 x 1.5mm ²																			
Earth Terminal Capacity 3	3 x 2.5mm ²																			
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand																			
Earth Terminal Capacity 5	1 x 6mm ²																			
Product Class 1	Must be earthed (ref BS7671 415.2.1)																			
Ambient Operating Temperature	-5° to +40°C																			
Recommended Location	Internal Use Only																			
Maximum Installation Altitude	2000m																			
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)																			
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755																			
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:40 AM E&OE																		

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM11238