Hamilton

making connections beautifully

| | Wiring Accessories • Circuit Protection • Sr | nart Lighting Control & Multi-room Audio |
|---|--|--|
| <u>82CR312SB-W</u> | | |
| Sheer CFX Satin Brass 1 gang 20AX Intermediate Rocker Satin Brass/White | | |
| | | |
| Item Image | Wiring | Dimensions |
| - | | |
| | 2 Way Switch Switch 2 Way Switch L10L2 L2 L2 L1 L1 L1 L1 L2 L2 L1 L1 L2 L2 L2 | Hemilton SHEER CFX R312 Intermediate Rocker |
| | | |
| Primary Range | Sheer CFX - Designed to fit Folded Metal Wall Box Enclosure | es that comply with BS4662-2006. |
| Insert Type | Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006. 1 gang 20AX Intermediate Rocker | |
| Plate Finish | Sheer CFX Satin Brass | |
| Insert Colour | | |
| | Satin Brass/White | |
| EAN13 Barcode | 5017504023348 | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 25mm | |
| Switched Poles | Single | |
| Current Rating | 20AX | |
| Voltage | 220/250V AC | |
| Maximum Load | 20 Amp inductive | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 5 x 1mm2 | |
| Terminal Capacity 2 | 4 x 1.5mm2 | |
| Terminal Capacity 3 | 2 x 2.5mm2 | |
| Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Terminal Capacity 5 | 1 x 6mm2 | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed | |
| | | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval Patents and Trademarks | BS EN 60669-1 CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 10:41 A E&C |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Of | | Listed in Trimble Product selector |

E: info@hamilton-litestat.com www.hamilton-litestat.com

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio