SL


making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


82CSS1SB-B

Sheer CFX Satin Brass 1 gang 13A Double Pole Switched Socket Satin Brass/Black

Item Image







Dimensions



Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.		
Insert Type	1 gang 13A Double Pole Switched Socket		
Plate Finish	Sheer CFX Satin Brass		
Insert Colour	Satin Brass/Black		
EAN13 Barcode	5017504022013		
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mr	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Switched Poles	Double		
Current Rating	13 Amp		
Voltage	220/250V AC		
Maximum Load	13 Amp		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	3mm		
Terminal Capacity 1	4 x 2.5mm2		
Terminal Capacity 2	3 x 4mm2		
Terminal Capacity 3	2 x 6mm2 Multi-Strand		
Terminal Capacity 4	1 x 10mm2		
Earth Terminal Capacity 1	4 x 2.5mm2		
Earth Terminal Capacity 2	3 x 4mm2		
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand		
Earth Terminal Capacity 4	1 x 10mm2		
Product Class 1	Must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS 1363-2		
Additional Notes	Dual Earth: Yes		
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 17 October 2018 10:41 AM E&OE	

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









