SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

82DJ45B

Sheer Floor Satin Brass 1 gang RJ45 CAT 5E Outlet - Unshielded Black

Primary Range Primary Range Insert Type Plate Finish Insert Colour EAN13 Barcode Dimensions (Nominal) Weight Fixing Hole Centres Primary Range Sheer Floor Sockets 1 gang RJ45 CAT 5E Black 5028690041115 Single: Height = 93 Weight Fixing Hole Centres

Rear View R.4.5 CATSe and CATS Wiring Codeur Codes


Pin LH. Wiring Schoolse Codeur Codeur

Pin LH. Wiring Schoolse Codeur Codeur

Pin LH. Wiring Schoolse Codeur Codeur

Pin LH. Wiring Schoolse Codeur

Pin LH. Wiring



Primary Range	Sheer Floor Sockets	
Insert Type	1 gang RJ45 CAT 5E Outlet - Unshielded	
Plate Finish	Sheer Floor Box Satin Brass	
Insert Colour	Black	
EAN13 Barcode	5028690041115	
Dimensions (Nominal)	Single: Height = 93.5mm Width = 85.5mm Depth = 3.0mm (6.5mm Hinged Cover)	
Weight	206 GR	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
EuroFix Additional Notes	Can be used in both EIA 568A and EIA 568B wiriing schedules	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 17 October 2018 11:27 AM E&OE

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











