## Hamilto

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 82DPNCSB-W Sheer Satin Brass 1 gang 20AX Double Pole Rocker and Neon and Cable Outlet Satin Brass/White Item Image Wiring Dimensions Hamilton DPNC Double Pole Rocker & Neon & Cable Outlet 86.0 1.5 18.5 60.3 A ..... arth ive Ø11.0 Primary Range Sheer Insert Type 1 gang 20AX Double Pole Rocker + Neon + Cable Outlet Plate Finish Sheer Box Satin Brass Insert Colour Satin Brass/White EAN13 Barcode 5017503043859 Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm Dimensions (Nominal) **Fixing Hole Centres** Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 20AX 220/250V AC Voltage 20 Amp inductive Maximum Load Mains Frequency 50Hz IP2XD IP Rating Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2 5mm2 **Terminal Capacity 2** 2 x 4mm2 Multi Strand **Terminal Capacity 3** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed -5° to +40°C Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm<sup>2</sup> Max = 2.5mm<sup>2</sup> Standard/Approval BS EN 60669-1 Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is as part of our development programme correct at the time of going to press. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 09:58 AM Illustrations and diagrams are reproduced within the limitations of reproduction and printing E&OE process and are not binding of certain finishes R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimble SECA

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com E' info@

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

SL