

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

84C1X2V

Remain Range Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that correly with 834602-2006. Insert Type 1 gang 2009A inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Partie Finish Sheet CFX Shin Sheet CFX Shin Sheet Shin Steel Shin Steel Shin Sheet CFX Shin Sheet Shin Sheet CFX Shin Sheet Shin Sheet CFX Shin Sheet Shin Shin Shin Shin Shin Shin Shin Shin	Sheer CFX Satin Steel 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Satin Steel			
Primary Range Sheer CFX - Designed to 8t Folded Metal Wall Box Enclosures that comply with 854682-2006. Insert Type 1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Sheer CFX Skill Sheel Insert Good San Skeel EAN1 58 Barcode 56175040838110 Sheer CFX Skill Sheel Insert Good San Skeel EAN1 58 Barcode 56175040838110 Sheer CFX Skill Sheel Insert Good San Skeel EAN1 58 Barcode 56175040838110 Sheer CFX Skill Sheel Insert Good San Skeel EAN1 58 Barcode 56175040838110 Sheer CFX Skill Sheel Insert Good San Skeel EAN1 58 Barcode 56175040838110 Sheer CFX Skill Sheel Insert Good San Skeel EAN1 58 Barcode 56175040838110 Sheer CFX Skill Sheel Insert Good San Skeel EAN1 58 Barcode 56175040838110 Sheer CFX Skill Sheel Sheel Sheer CFX Skill Sheel Sheel Sheer CFX Skill Sheel Sheel Sheel CFX Skill Sheel Sheel Sheel CFX Skill She	Item Image	Wiring	Dimensions	
Paste Type		LOOF IN LOOF OUT TWO MAY SWITCHISG MICHIGAN MICHIGAN LORE LOF IN LOOF OUT TWO MAY SWITCHISG MICHIGAN LOF IN LOOF OUT TWO MAY SWITCHISG MICHIGAN LOF IN LOOF OUT TWO MAY SWITCHISG LOF IN LOF IN LOOF OUT TWO MAY SWITCHISG LOF IN LOF IN LOOF OUT TWO MAY SWITCHISG LOF IN LOF IN LOOF OUT TWO MAY SWITCHISG LOF IN LOF IN LOF IN LOOF OUT TWO MAY SWITCHISG LOF IN LOF IN LOF IN LOOF OUT TWO MAY SWITCHISG LOF IN LOF IN LOF IN LOOF OUT TWO MAY SWITCHISG LOF IN LOF IN LOF IN LOF IN LOOF OUT TWO MAY SWITCHISG LOF IN LOF IN LOF IN LOF IN LOF IN LOOF OUT TWO MAY SWITCHISG LOF IN LOF IN LOF IN LOF IN LOF IN LOF IN LOOF OUT TWO MAY SWITCHISG LOF IN LOOF OUT TWO MAY SWITCHISG LOF IN LOF IN LOF IN LOF IN LOF IN L	SHEER CFX 1X2V Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer	
Plate Finish Insert Colour Satin Steel Insert Colour Satin Steel Insert Colour Satin Steel EAN13 Barcode Soft7594039110 Dimensions (Nominal) Singles: Height = 88.0mm Width = 88.0mm Depth = 1.5mm plate + 3.0mm gasket Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 200VA (low voltage) Switched Poles Current Rating 0.8 Amp Voltage 220250V AC Voltage 220250V AC Wains Frequency Soft- P Rating IPZXD Contact Gap Minimum None Terminal Capacity 1 2x 1.5mm2 Earth Terminal Capacity 1 2x 1.5mm2 Earth Terminal Capacity 1 5x 1.mm2 Earth Terminal Capacity 2 4x 1.5mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 4 1x 4.mm2 Multi-strand Earth Terminal Capacity 5 Frouduc Class 1 5x 6mc2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Earth Earth Earth Earth Earth Earth Ea	Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.		
Insert Colour EAN13 Barcode S9175040393110 Dimensions (Nomina) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 200VA (low voltage) Switched Poles Single Current Rating 0.8 Amp Voltage 220/256V AC Maximum Load 300VA ((low voltage) Min Load 25VA Maximum Load 400VA ((low voltage) Min Load 25VA Maximum Load 300VA ((low voltage) Min Load 25VA Maximum Load 400VA ((low voltage) Min Load 25VA 400VA ((low voltage) Mi	Insert Type	1 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer		
EAN13 Barcode 5017504039110 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 200VA (tow voltage) Switched Poles Single Current Rating 0.8 Amp Voltage 220256V AC Waximum Load 200VA (low voltage) Min Load 25VA Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum None Terminal Capacity 1 2 x 1.5mm2 Earth Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 9 Earth Ter	Plate Finish	Sheer CFX Satin Steel		
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Fixing + 96.03mm Grid Fixing = CFX Clips Minimum Wall Box Depth 3.5mm Wattage 200VA (low voltage) Switched Poles Single Current Rating 0.8 Amp Voltage 2207250V AC Maximum Load Maximum Installation Altitude Standard/Approval Bas En 6069-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. Not company to improve products the manufactured of the transformer to contact the installation Altitude Patents and Trademarks CFX is a Registered Trade Mark No. 2396607 Trade Mark No. 23965075 Sheet CFX is a Registered Design under Reference Nos. 2300764 SSZ =3020755 All products listed conform to current British or European bankaria and the product information as contract in the line of groys to press. All products listed conform to current British or European bankaria and the products information as contract in the line of groys to press. All products listed conform to current British or European bankaria and the products information as contract in the line of groys to press. All products listed conform to current British or European bankaria and the products information as contract the line of groys to press. All products listed conform to current	Insert Colour			
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Fixing + 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 9.5mm Wattage 200VA (low voltage) Switched Poles Single Current Rating 0.8 Amp Voltage 220/250V AC Maximum Load 200VA (low voltage) Min Load 25VA Maximum Load Mains Frequency 19 Rating 19 P2XD Contact Gap Minimum None 10 P2XD Contact Gap	EAN13 Barcode	5017504039110		
Minimum Wall Box Depth 35mm Wattage 200VA (low voltage) Switched Poles Current Rating 0.8 Amp Voltage 220/250V AC Maximum Load 200VA (low voltage) Min Load 25VA Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum None Terminal Capacity 1 2 x 1mm2 Terminal Capacity 1 2 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 3-5* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDSE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75%- please contact our Technical for compatibility. NOTE: it is recommended to contact the manufacture of the transformer to confirm that it is dimmable and is considered to be an inductive load. CFX is a Registered Design under an accretical manufacture of the transformer to confirm that it is dimmable and is considered to be an inductive load. CFX is a Registered Trade Mark No 2398667 Trade Mark on 2296588 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of ging to press and are remandactured under an accretical is it is the policy of the company to improve products as pain of our development programme. Therefore, we reserve the right to all and designs and dimensions without prior notice. But the manufacturing processes we cannot guarantee an exact colour match and shadings of certain finisher.	Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket		
Minimum Wall Box Depth 35mm Wattage 200VA (low voltage) Switched Poles Current Rating 0.8 Amp Voltage 220/250V AC Maximum Load 200VA (low voltage) Min Load 25VA Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum None Terminal Capacity 1 2 x 1mm2 Terminal Capacity 1 2 x 1mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 3-5* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDSE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75%- please contact our Technical for compatibility. NOTE: it is recommended to contact the manufacture of the transformer to confirm that it is dimmable and is considered to be an inductive load. CFX is a Registered Design under an accretical manufacture of the transformer to confirm that it is dimmable and is considered to be an inductive load. CFX is a Registered Trade Mark No 2398667 Trade Mark on 2296588 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of ging to press and are remandactured under an accretical is it is the policy of the company to improve products as pain of our development programme. Therefore, we reserve the right to all and designs and dimensions without prior notice. But the manufacturing processes we cannot guarantee an exact colour match and shadings of certain finisher.				
Wattage 200VA (low voltage) Switched Poles Single Ourrent Rating 0.8 Amp Voltage 220/250V AC Maximum Load 200VA (low voltage) Min Load 25VA Maximum Load 200VA (low voltage) Min Load 25VA Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum None Terminal Capacity 1 2 x 1mm2 Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60689-1 LEADING EOGE TECHNOLOGY DIMMERS for use with low voltage toroldal transformers and some LED lamps. When additional Notes Patents and Trademarks CPX is a Registered Trade Mark Not 20396667 Trade SS 2 s020755 All products listed conform to current British or Europeon standard and the product information is considered trade for the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks All products listed conform to current British or Europeon standard and the product information is considered for the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks All products listed conform to current British or Europeon standard and the product information is considered for the transformer to confirm that it is dimmable and is considered to be an inductive load. EXCENT Set as Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or Europeon standard and the product information is context at the time of going to press. All products listed conform to current British or Europeon standard and the productive formation is context at the time of going to press. All products listed conform to current British or Europeon standard and the produ				
Current Rating 0.8 Amp Voltage 220/250V AC Maximum Load 200VA (low voltage) Min Load 25VA Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature 5 to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Additional Notes LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-taled by 75% - please contact our Technical for compatibility. NOTE: it is recommended to contact the manufacture of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020764 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. British Technical For company to improve products and dimensions without prior notice. British Technical For an accredited Ses EN ISO 9001 : 2015 Quality Management System. CFX is a Registered Trade Mark No 2398667 T		200VA (low voltage)		
Voltage 220/250V AC Maximum Load 200VA (low voltage) Min Load 25VA Maxims Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 2 x 1mm2 Terminal Capacity 1 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Forduct Class 1 1 Face plate must be earthed Ambient Operating Temperature 5 to 4 4 0°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE: it is recommended to contact the manufacture of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No 2398670 Trade Mark N				
Maximum Load 200VA (low voltage) Min Load 25VA Mains Frequency 50Hz IP Rating IP Ra	Current Rating			
Mains Frequency Frequ	Voltage			
IP Rating		200VA (low voltage) Min Load 25VA		
Contact Gap Minimum None Terminal Capacity 1 2 x 1mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes ELADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No. 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of gling to press. All products listed conform to current British or European standard and the product information is correct at the time of gling to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Certain firmish or Certain firmish or Certain at 17 October 2018 10.41 AM E&OE or certain firmish and shadings of Certain firmish or Certain fir	Mains Frequency	50Hz		
Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 I x 4mm2 Multi-strand Earth Terminal Capacity 4 Earth Terminal Capacity 4 I x 4mm2 Multi-strand Earth Terminal Capacity 5 Face plate must be earthed Ambient Operating Temperature Face plate must be earthed Face p	IP Rating	IP2XD		
Earth Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Todacity 5 Product Class 1 Ambient Operating Temperature Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE: it is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. CFX is a Registered Trade Mark No. 2398667 Trade Mark No. 2296686 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to the policy of the company to improve products as a part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 10.41 AM guarantee an exact colour match and shadings of of certain finishes.	Contact Gap Minimum	None		
Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE: it is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. Correct as at 17 October 2018 10:41 AM guarantee an exact colour match and shadings of certain finishes.	Terminal Capacity 1	2 x 1mm2		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature 7-5° to +40°C Recommended Location Maximum Installation Altitude Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE: It is recommended to contact the manufacture of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot and dimensions without prior notice. Correct as at 17 October 2018 10:41 AM EACE Correct as an 4 not blonding.	Terminal Capacity 2	2 x 1.5mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE: it is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BEN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 10:41 AM E&OE	Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 4mm2 Multi-strand 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No. 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are munifactured under an accredited as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All accessories are manufacturing processes we cannot Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All accessories are manufacturing processes we cannot Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.		1 x 4mm2 Multi-strand		
Product Class 1 Ambient Operating Temperature Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE: It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.		1 x 6mm2		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. Correct as at 17 October 2018 10:41 AM guarantee an exact colour match and shadings of certain finishes.		Face plate must be earthed		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No. 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.		-5° to +40°C		
Maximum Installation Altitude Standard/Approval BS EN 6069-1 Additional Notes LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No. 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Ullustrations and diagrams are reproduced within the limitations of reproduction and printing processes and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.				
Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks CFX is a Registered Trade Mark No. 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 10:41 AM E&OE				
Additional Notes LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE: It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 10:41 AM E&OE of certain finishes.		BS EN 60669-1		
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 10:41 AM E&OE of certain finishes.		LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to after designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 10:41 AM E&OE	Patents and Trademarks			
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of of certain finishes.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio