Item Image



making connections beautifully

Dimensions

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

84C4XTSSS-B

Sheer CFX Satin Steel 4 gang Multi-Way Touch Slave Controller Satin Steel/Black

Wiring

Hamilton 4XTS
Multi-WayTouch Slave Controller Multi- Way Wiring using Slave module(s) Primary Range Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006. Insert Type 4 gang Multi-Way Touch Slave Controller Plate Finish Sheer CFX Satin Steel Insert Colour Satin Steel/Black EAN13 Barcode 5017504025885 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage The same as Touch Master or Ceiling Dimmer Switched Poles N/A Current Rating The same as Touch Master or Ceiling Dimmer 220/250V AC Voltage Maximum Load The same as Touch Master 50Hz Mains Frequency IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C **Ambient Operating Temperature**

process and are not binding. of ce
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

All products listed conform to current British or European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing

Recommended Location

Patents and Trademarks

Standard/Approval

Additional Notes

Maximum Installation Altitude

+44 (0)1747 860088 F: +44 (0)1179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84

Internal Use Only

BS EN 60669-2-1

used with Touch Master Dimmers

CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of

of certain finishes

Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755

2000m



Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be





It is the policy of the company to improve products as part of our development programme.

Therefore, we reserve the right to alter designs and dimensions without prior notice.



Correct as at 17 October 2018 10:41 AM







Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio