

making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

84C4XTSSS-W


Sheer CFX Satin Steel 4 gang Multi-Way Touch Slave Controller Satin Steel/White

Item Image

Wiring



Dimensions



Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.
Insert Type	4 gang Multi-Way Touch Slave Controller
Plate Finish	Sheer CFX Satin Steel
Insert Colour	Satin Steel/White
EAN13 Barcode	5017504025892
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Wattage	The same as Touch Master or Ceiling Dimmer
Switched Poles	N/A
Current Rating	The same as Touch Master or Ceiling Dimmer
Voltage	220/250V AC
Maximum Load	The same as Touch Master
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	N/A
Terminal Capacity 1	2 x 1mm2
Terminal Capacity 2	2 x 1.5mm2
Earth Terminal Capacity 1	5 x 1mm2
Earth Terminal Capacity 2	4 x 1.5mm2
Earth Terminal Capacity 3	3 x 2.5mm2
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand
Earth Terminal Capacity 5	1 x 6mm2
Product Class 1	Face plate must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS EN 60669-2-1
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755
All products listed conform to current British or European standard and the product information is	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BY EN ISO 9001 : 2015 Quality Management System. BY EN ISO 9001 : 2015 Quality Management System. Therefore we reserve the right to alter designs

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

correct at the time of going to press.

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84







Therefore, we reserve the right to alter designs and dimensions without prior notice.





Correct as at 17 October 2018 10:41 AM





Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio