## Hamilton

## making connections beautifully

SL

SL	Thaking connections beautifully		
Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio			
	84CDSAT+W		
Observ OEV Ostin Otsel New Jackste			
Sheer CFX Satin Steel Non-Isolate	d TV+FM+SAT1+SAT2 Quadplexer 2in/4out	+1VF+1CS (DAB Compatible) white	
Item Image	Wiring	Dimensions	
SATI SATZ SATZ SATZ SATZ SATZ SATZ SATZ SATZ	Cable Clamp Screw Cable Clamp Screw Terminal Conductor, screwing the company of the company of t	Lippoilt or	
		HEINILON SHEER CFX DSAT+ Non-Isolated TV/FM/Satellite1/Satellite2 Quadplexer 2in/4out + TVF + TCS	
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.		
Insert Type	Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out +TVF+TCS (DAB Compatible)		
Plate Finish	Sheer CFX Satin Steel		
Insert Colour	White		
EAN13 Barcode	5017504030094		
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket		
Fixing Hole Centres	Box Fixing = 120.6mm         Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Switched Poles	N/A		
IP Rating	IP2XD		
Contact Gap Minimum	N/A		
Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 2	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 4mm2 Multi-strand		
Product Class 1	Must be earthed (ref BS7671 415.2.1)		
	-5° to +40°C		
Ambient Operating Temperature Recommended Location			
	Internal Use Only		
Maximum Installation Altitude EuroFix Additional Notes	2000m Quadplexer for use with combined TV FM and Satellite Signals (DAB compatible) plus Telephone Slave and Female TV Socket		
Frequencies 1	TV=5-68 MHz 125-860 MHz		
Frequencies 2	FM=88-108 MHz		
Frequencies 3	SAT DC=950-2200 MHz		
Frequencies 4	TV DC=5-2200 MHz		
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:41 AM E&OE	
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered	Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84	Listed in Trimble product selector DisSPlus (Ett. No. 1/1128)	