Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio
<u>84CR232SS-W</u> Sheer CFX Satin Steel 3 gang 20AX 2 Way Rocker Satin Steel/White		
		•
		R232 2 Way Rocker
	Administra 2 way setting	
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosure	es that comply with BS4662-2006.
Insert Type	3 gang 20AX 2 Way Rocker	
Plate Finish	Sheer CFX Satin Steel	
Insert Colour	Satin Steel/White	
EAN13 Barcode	5017504037383	
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	25mm	
Switched Poles	Single	
Current Rating	20AX	
Voltage	220/250V AC	
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	2 x 2.5mm2	
	2 x 4mm2 Multi-strand	
Terminal Capacity 4 Terminal Capacity 5	1 x 6mm2	
	6 x 1mm2	
Earth Terminal Capacity 1	5 x 1.5mm2	
Earth Terminal Capacity 2	5 X 1.5mm2 3 X 2.5mm2	
Earth Terminal Capacity 3	2 x 4mm2 Multi-strand	
Earth Terminal Capacity 4	1 x 6mm2	
Earth Terminal Capacity 5 Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only 2000m	
Maximum Installation Altitude		
Standard/Approval	BS EN 60669-1	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All accessories are manufactured under an accredited It is the policy of the company to improve products	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	The following of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:41 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville R T: +44 (0)1747 880088 F: +44 (0)1179 710414 Registered C E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in	oad, Brislington, Bristol, BS4 5NZ Jffice 1 Rushmills, Bedford Road, Northampton NN4 7YB 1 London No. 941624 VAT Registration No. 222 6607 84	Listed in Strinble LUCKINS Product Selector

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio