Hamilton

making connections beautifully

B4CR23SS-B Sheer CFX Satin Steel 3 gang 10AX 2 Way Rocker Satin Steel/Black Item Image Wiring Dimensions Image Image Image Image Primary Range Sheer CYX - Designed to fit Folded Metal Wall Base Enclosures that comply with B24862-2006. Image Intent Type 3 gang 10AX 2 Way Rocker Pela Pela Pinary Range Sheer CYX - Designed to fit Folded Metal Wall Base Enclosures that comply with B24862-2006. Image Intent Type 3 gang 10AX 2 Way Rocker Pela Pela Pinary Mange Sakin Skeel/Basek Edonm Edonm Edonm Insert Codu Sakin Skeel/Basek Edonm Edon Edonm Edonm		Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio		
Item Image Wiring Dimensions Image Image Image Image Image Image	84CR23SS-B				
Item Image Wiring Dimensions Image Image Image Image Image Sheer CPX - Designed to It Proided Metal Wall Box Enclosures that compty with BS4662-2006. Image Sheer CPX - Designed to It Proided Metal Wall Box Enclosures that compty with BS4662-2006. Image Sheer CPX - Statis Steel Image Sheer CPX Statis Steel Image Sheer CPX Statis Steel Image Sheer CPX Statis Steel Image Statis Steel Steel Imat					
Pimary RangeSheer CFX - Designed to It Folded Meal Wall Box Enclosures that comply with B54662-2006.Pimary RangeSheer CFX - Designed to It Folded Meal Wall Box Enclosures that comply with B54662-2006.Invent Type3 gang 10AX 2 Way RockorPlate Finish3 beer CFX Sain SelelInvent TypeSheer CFX - Designed to It Folded Meal Wall Box Enclosures that comply with B54662-2006.Invent Type3 gang 10AX 2 Way RockorPlate FinishSheer CFX Sain SelelInvent TypeSonge: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasketWaight150 GRFinigh Hole CentriesBox Fixing = 60.3mm Gnd Fixing = CFX ClipsMinimur Mull Box Depth25mmSoltched PolosSingleCurront Raing10AXVoltage220220V ACMaximur Ladd10 Arag inductiveMains Tenguancy504zIP Raing192XOContext Gap Minimur3mmTerminal Capacity 31 X 2.5mm2Terminal Capacity 31 X 2.5mm2Terminal Capacity 31 X 2.5mm2Terminal Capacity 31 X 2.5mm2Terminal Capacity 41 X 1.5mm2Terminal Capacity 51 X 4mm2Terminal Capacity 51 X 4mm2Enth Terminal Capacity 51 X 4mm2Enth Terminal Capacity 51 X 4mm2Enth Terminal Capacity 61 X 4mm2Enth Terminal Capacity 51 X 4mm2 </th <th></th> <th></th> <th></th>					
ImageSheer CFX - Designed to ft Folded Metal Wall Box Enclosures that comply with BS4662-2000.Pinnary RangeSheer CFX - Designed to ft Folded Metal Wall Box Enclosures that comply with BS4662-2000.Insert Type3 gang 10AX 2 Way RockarPitoe FinlohSheer CFX Satin SkeelInsert ColorSath SteelBlackEANT S Barcode5017560408632Dimensions (Normal)Single: Height = 80.mm Width = 86.0mm Degth = 1.5mm plate + 3.0mm gasketWeight150 GRFinloh DegthSingle: Height = 80.mm Midth = 86.0mm Degth = 1.5mm plate + 3.0mm gasketMeninum Wall Box DegthSingleSinder GoldenSingleKinder DegthSingleMinnum Wall Box DegthSingleSinder GoldenSingleCarrent Rating10 AARVoltage220250V ACMains Frequency60 KrMains Frequency60 KrJerninal Capacity 15 x fmm2Terminal Capacity 21 x fsmm2Terminal Capacity 31 x fsmm2Terminal Capacity 41 x fsmm2Carrent Rating3 x fsmm2Earth Terminal Capacity 51 x fsmm2Earth Terminal Capacity 61 x fsmm2Earth Terminal Capacity 61 x fsmm2Earth Terminal Capacity 7 <td< th=""><th>Item Image</th><th>Wiring</th><th>Dimensions</th></td<>	Item Image	Wiring	Dimensions		
Line Line Line Line Line Line Line Line			R23		
Insert Type 3 gang 10AX 2 Way Rocker Plate Finish Sheer CFX Satin Steel Insert Colour Satin Steel/Black EAN13 Barcode 5017504036232 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Maing Frequency 50Hz Paraller 19XDO Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 25mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 3 x 25mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2		Attended 2 very westing			
Plate Finish Sheer CFX satin Steel Insert Colour Satin Steel/Black EAN13 Barcode Sirjde: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Weigh 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimur Wall Box Depth 25mm Switched Poles Single: Current Rating 10AX Voltage 20/250V AC Maximur Load 10 Amp inductive Mains Frequency 504Z Pating 10AX Voltage 20/250V AC Maximur Load 10 Amp inductive Mains Frequency 504Z Pating 192XD Contact Gap Minimur 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 4zmm2 Multi-strand Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capa	Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosure	es that comply with BS4662-2006.		
Insert ColourSatin Steel/BlackEAN13 Barcode5017504036232Dimensions (Nominal)Single: Height = 86.0mm Widh = 86.0mm Depth = 1.5mm plate + 3.0mm gasketWeight150 GRFixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX ClipsMinimum Wall Box Depth25mmSwitched PolesSingleCurrent Rating10AXVoltage220/250V ACMaximum Load10 Amp inductiveMains Frequency60HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 4mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 53 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 4mm2 Multi-strandEarth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 75 x 140°CRecormmended LocacionHearthedArbient Operating Temp	Insert Type	3 gang 10AX 2 Way Rocker			
EAN13 Barcode 5017504036232 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mainum Load 10 Amp inductive Mainum Load 10 Amp inductive Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand					
Dimensions (Nominal) Single: Height = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10Ax Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 1 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Earth Terminal Capacity 4 1 x 4mm2 Earth Terminal Capacity 4 1 x 4mm2	Insert Colour				
Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2	EAN13 Barcode				
Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2	Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm	n plate + 3.0mm gasket		
Fixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX ClipsMinimum Wall Box Depth25mmSwitched PolesSingleCurrent Rating10AXVoltage220/250V ACMaximum Load10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 4mm2Earth Terminal Capacity 43 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 71 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 71 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 71 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 71 x 6mm2Earth Terminal Capacity 81 x 6mm2Earth Terminal Capacity 91 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 71 x 6mm2Earth Terminal Capacity 81 x 6mm2Earth Terminal Capacity 91 x					
Minimum Wall Box Depth25mmSwitched PolesSingleCurrent Rating10AXVoltage220/250V ACMaximum Load10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 51 x 6mm2Freduct Class 1Must be earthedAmbient Operating Temperature5° to 440°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m					
Switched PolesSingleCurrent Rating10AXVoltage220/250V ACMaximum Load10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Terminal Capacity 31 x 6mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 4mm2 Multi-strandEarth Terminal Capacity 75 x 1mm2Earth Terminal Capacity 61 x 4mm2 Multi-strandEarth Terminal Capacity 75 x 10mm2Earth Terminal Capacity 61 x 4mm2 Multi-strandEarth Terminal Capacity 75 x 10mm2Earth Terminal Capacity 61 x 4mm2 Multi-strandEarth Terminal Capacity 75 x 10mm2Earth Terminal Capacity 61 x 6mm2Recommended LocationMust be earthedAmbient Operating Temperature-5" to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m					
Current Rating10AXVoltage220/250V ACMaximum Load10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 6mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 61 x 6mm2Earth Terminal Capacity 75 % to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m		Single			
Voltage220/250V ACMaximum Load10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 11 x 4mm2 Multi-strandEarth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be eartheedAmbient Operating Temperature-5" to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Current Rating	-			
Maximum Load10 Amp inductiveMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 6mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandConsci y 33 x 2.5mm2Earth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	-				
Mains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 6mm2Earth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 41 x 4.15mm2Earth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m					
IP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 41 x 6mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m	Mains Frequency				
Contact Gap Minimum3mmTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Earth Terminal Capacity 53 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m					
Terminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 53 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m					
Terminal Capacity 24 x 1.5mm2Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m		5 x 1mm2			
Terminal Capacity 31 x 2.5mm2Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m		4 x 1.5mm2			
Terminal Capacity 41 x 4mm2 Multi-strandTerminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m					
Terminal Capacity 51 x 6mm2Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m					
Earth Terminal Capacity 15 x 1mm2Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m					
Earth Terminal Capacity 24 x 1.5mm2Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m		5 x 1mm2			
Earth Terminal Capacity 33 x 2.5mm2Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m					
Earth Terminal Capacity 41 x 4mm2 Multi-strandEarth Terminal Capacity 51 x 6mm2Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000m					
Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m		1 x 4mm2 Multi-strand			
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m		1 x 6mm2			
Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Product Class 1	Must be earthed			
Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Ambient Operating Temperature	-5° to +40°C			
		Internal Use Only			
Standard/Approval BS EN 60669-1	Maximum Installation Altitude	2000m			
	Standard/Approval	BS EN 60669-1			

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

84CR23SS-B

Sheer CFX Satin Steel 3 gang 10AX 2 Way Rocker Satin Steel/Black

Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:41 AM E&OE
	dad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84	Listed in Trimble. LUCKINS Product selector

SL