Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sn	mart Lighting Control & Multi-room Audio
	84CR26SS-B	
Shoor CEX	Satin Steel 6 gang 10AX 2 Way Rocker Sati	n Stool/Block
Item Image	Wiring	Dimensions
		Hemilton SHEER CFX R26 2 Way Rocker
	Image: set of the set of th	
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosure	es that comply with BS4662-2006
Insert Type	6 gang 10AX 2 Way Rocker	
Plate Finish	Sheer CFX Satin Steel	
Insert Colour	Satin Steel/Black	
EAN13 Barcode	5017504036201	
	Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket	
Dimensions (Nominal)	Box Fixing = 120.6mm Grid Fixing = CFX Clips	
Fixing Hole Centres		
Minimum Wall Box Depth	25mm Single	
Switched Poles	Single	
Current Rating	10AX	
Voltage	220/250V AC	
Maximum Load	10 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	1 x 2.5mm2	
Terminal Capacity 4	1 x 4mm2 Multi-strand	
Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:41 AI E&O
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered	Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB In London No. 941624 VAT Registration No. 222 6607 84	Listed in Strimbe LUCKINS Relector DSPlus Cott. No. 141138

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio