





84DJ12B

Sheer Floor Satin Steel 1 gang RJ12 Outlet - Unshielded Black

| Item Image | Wiring | Dimensions | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|--------------|------------|--------------|---|----------|----------|----------|---|---------------|------|--|---|----------------|--------|--|---|--------------|-------|--|---|--------------|-----|--|---|----------------|-------|--|---|----------|----------|--|---|----------|----------|--|-----------------------------------------------------------------------------------------------------------------------------------|
|  | <p style="text-align: center;">Wiring</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p><small>Datacom Module Rear View RJ11 / 12 Socket Rear View</small></p>  </div> <div style="text-align: center;"> <p><small>View of Transparent Cover</small></p>  </div> </div> <p style="text-align: center;"><small>Cable tie anchor</small></p> <table border="1" style="margin-left: auto; margin-right: auto; font-size: 8px;"> <thead> <tr> <th>Pin</th> <th>Color</th> <th>Wire Color</th> <th>Other Socket</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>NOT USED</td> <td>NOT USED</td> <td>NOT USED</td> </tr> <tr> <td>2</td> <td>GREEN / White</td> <td>BLUE</td> <td></td> </tr> <tr> <td>3</td> <td>ORANGE / White</td> <td>YELLOW</td> <td></td> </tr> <tr> <td>4</td> <td>WHITE / Blue</td> <td>GREEN</td> <td></td> </tr> <tr> <td>5</td> <td>BLUE / White</td> <td>RED</td> <td></td> </tr> <tr> <td>6</td> <td>WHITE / Orange</td> <td>BLACK</td> <td></td> </tr> <tr> <td>7</td> <td>NOT USED</td> <td>NOT USED</td> <td></td> </tr> <tr> <td>8</td> <td>NOT USED</td> <td>NOT USED</td> <td></td> </tr> </tbody> </table> | Pin | Color | Wire Color | Other Socket | 1 | NOT USED | NOT USED | NOT USED | 2 | GREEN / White | BLUE | | 3 | ORANGE / White | YELLOW | | 4 | WHITE / Blue | GREEN | | 5 | BLUE / White | RED | | 6 | WHITE / Orange | BLACK | | 7 | NOT USED | NOT USED | | 8 | NOT USED | NOT USED | | <p style="text-align: center;">Dimensions</p>  |
| Pin | Color | Wire Color | Other Socket | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | NOT USED | NOT USED | NOT USED | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | GREEN / White | BLUE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | ORANGE / White | YELLOW | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | WHITE / Blue | GREEN | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | BLUE / White | RED | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | WHITE / Orange | BLACK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 | NOT USED | NOT USED | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | NOT USED | NOT USED | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Primary Range | Sheer Floor Sockets | |
| Insert Type | 1 gang RJ12 Outlet - Unshielded | |
| Plate Finish | Sheer Floor Box Satin Steel | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017504034733 | |
| Dimensions (Nominal) | Single: Height = 93.5mm Width = 85.5mm Depth = 3.0mm (6.5mm Hinged Cover) | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = N/A | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | N/A | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 1 | 5 x 1mm ² | |
| Earth Terminal Capacity 2 | 4 x 1.5mm ² | |
| Earth Terminal Capacity 3 | 3 x 2.5mm ² | |
| Earth Terminal Capacity 4 | 1 x 4mm ² Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm ² | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| EuroFix Additional Notes | Can be used as either RJ11 (4 wires) or RJ12 (6 wires) | |
| <p style="font-size: 8px;">All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p> | <p style="font-size: 8px;">All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p> | <p style="font-size: 8px;">It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p> |
| <p style="font-size: 8px;">Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p> | <p style="font-size: 8px;">Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p> | <p style="text-align: right; font-size: 8px;">Correct as at 17 October 2018 11:27 AM E&OE</p> |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
 T: +44 (0)1747 860088 F: +44 (0)1179 710414
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
 Registered in London No. 941624 VAT Registration No. 222 6607 84

