making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


84R32WH-W

Sheer Satin Steel 2 gang 10AX Intermediate Rocker White/White


Item Image







Dimensions



Primary Range Insert Type 2 gang 10AX Intermediate Rocker Plate Finish Sheer Box Satin Steel Insert Colour White/White EAN13 Barcode 5017503060320 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz		
Plate Finish Insert Colour White/White EAN13 Barcode Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive		
Insert Colour		
EAN13 Barcode 5017503060320 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive		
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive		
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive		
Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive		
Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive		
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive		
Voltage 220/250V AC Maximum Load 10 Amp inductive		
Maximum Load 10 Amp inductive		
·		
Mains Fragues V		
Mains Frequency 50Hz	50Hz	
IP Rating IP2XD		
Contact Gap Minimum 3mm	3mm	
Terminal Capacity 1 5 x 1mm2	5 x 1mm2	
Terminal Capacity 2 4 x 1.5mm2	4 x 1.5mm2	
Terminal Capacity 3 1 x 2.5mm2		
Terminal Capacity 4 1 x 4mm2 Multi-strand		
Terminal Capacity 5 1 x 6mm2		
Earth Terminal Capacity 1 5 x 1mm2		
Earth Terminal Capacity 2 4 x 1.5mm2		
Earth Terminal Capacity 3 3 x 2.5mm2		
Earth Terminal Capacity 4 1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5 1 x 6mm2		
Product Class 1 Must be earthed		
Ambient Operating Temperature -5° to +40°C	-5° to +40°C	
Recommended Location Internal Use Only		
Maximum Installation Altitude 2000m		
Standard/Approval BS EN 60669-1		
Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586		
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to and dimensions without price		

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









Correct as at 17 October 2018 10:00 AM



Illustrations and diagrams are reproduced within

the limitations of reproduction and printing process and are not binding.