SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

84RRTSS-B

Sheer Satin Steel 1 gang 10AX Push To Make Retractive Rocker Satin Steel/Black







Dimensions

RRT Push to Make Retractive Rocker					
1		86.0 — 60.3 —		1.5 18.5	
86.0			•		

Primary Range	Sheer			
Insert Type	1 gang 10AX Push To Make Retractive Rocker			
Plate Finish	Sheer Box Satin Steel			
Insert Colour	Satin Steel/Black			
EAN13 Barcode	5017503066193			
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm			
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A			
Minimum Wall Box Depth	25mm			
Switched Poles	Single			
Current Rating	10AX			
Voltage	220/250V AC			
Maximum Load	10 Amp inductive			
Mains Frequency	50Hz			
IP Rating	IP2XD			
Contact Gap Minimum	3mm			
Terminal Capacity 1	5 x 1mm2			
Terminal Capacity 2	4 x 1.5mm2			
Terminal Capacity 3	1 x 2.5mm2			
Terminal Capacity 4	1 x 4mm2 Multi-strand			
Terminal Capacity 5	1 x 6mm2			
Earth Terminal Capacity 1	5 x 1mm2			
Earth Terminal Capacity 2	4 x 1.5mm2			
Earth Terminal Capacity 3	3 x 2.5mm2			
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand			
Earth Terminal Capacity 5	1 x 6mm2			
Product Class 1	Must be earthed			
Ambient Operating Temperature	-5° to +40°C			
Recommended Location	Internal Use Only			
Maximum Installation Altitude	2000m			
Standard/Approval	BS EN 60669-1			
Patents and Trademarks	Sheer is a Registered Trade Mark No. 2296586			
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Westerform and discourse as a second condition	Due to second outside a second outside a	0		

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









Correct as at 17 October 2018 10:00 AM

