




## 8645SS1SC-B

### Sheer Satin Chrome 45A Double Pole Rocker + Neon + 13A Switched Socket Red+Satin Chrome/Black

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|  |  |  |

|   |   |   |
|---|---|---|
| Primary Range   | Sheer   |   |
| Insert Type   | 45A Double Pole Red Rocker + Neon + 13A Switched Socket   |   |
| Plate Finish  | Sheer Box Satin Chrome  |   |
| Insert Colour   | Red+Satin Chrome/Black  |   |
| EAN13 Barcode   | 5017503086702   |   |
| Dimensions (Nominal)  | Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm   |   |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = N/A  |   |
| Minimum Wall Box Depth  | 35mm  |   |
| Switched Poles  | Double  |   |
| Current Rating  | Switch 45 Amp Socket 13 Amp   |   |
| Voltage   | 220/250V AC   |   |
| Maximum Load  | Switch 45 Amp Socket 13   |   |
| Mains Frequency   | 50Hz  |   |
| IP Rating   | IP2XD   |   |
| Contact Gap Minimum   | 3mm   |   |
| Terminal Capacity 1   | 3 x 6mm <sup>2</sup>  |   |
| Terminal Capacity 2   | 2 x 10mm <sup>2</sup>   |   |
| Terminal Capacity 3   | 1 x 16mm <sup>2</sup>   |   |
| Earth Terminal Capacity 1   | 3 x 6mm <sup>2</sup>  |   |
| Earth Terminal Capacity 2   | 2 x 10mm <sup>2</sup>   |   |
| Earth Terminal Capacity 3   | 1 x 16mm <sup>2</sup>   |   |
| Product Class 1   | Must be earthed   |   |
| Ambient Operating Temperature   | -5° to +40°C  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Standard/Approval   | BS 4177   |   |
| Patents and Trademarks  | Sheer is a Registered Trade Mark No. 2296586  |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.         | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 10:00 AM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84

