Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sr	nart Lighting Control & Multi-room Audio
<u>8645SS1WH-W</u> Sheer Satin Chrome 45A Double Pole Rocker + Neon + 13A Switched Socket Red+White/White		
Item Image	Wiring	Dimensions
		Hemilton SHEER 45551 Double Pole Red Rocker & Neon & 13A Switched Socket
Primary Range	Sheer	
Insert Type	45A Double Pole Red Rocker + Neon + 13A Switched Socker	t
Plate Finish	Sheer Box Satin Chrome	
Insert Colour	Red+White	
EAN13 Barcode	5017503080700	
Dimensions (Nominal)	Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm	
Fixing Hole Centres	Box Fixing = 120.6 mm Grid Fixing = N/A	
Minimum Wall Box Depth	35mm	
Switched Poles	Double	
Current Rating	Switch 45 Amp Socket 13 Amp	
Voltage	220/250V AC	
Maximum Load	Switch 45 Amp Socket 13	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	3 x 6mm2	
	2 x 10mm2	
Terminal Capacity 2		
Terminal Capacity 3	1 x 16mm2 3 x 6mm2	
Earth Terminal Capacity 1		
Earth Terminal Capacity 2	2 x 10mm2	
Earth Terminal Capacity 3	1 x 16mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C Internal Use Only	
Recommended Location		
Maximum Installation Altitude	2000m BS 4177	
Standard/Approval Patents and Trademarks		
All products listed conform to current British or	Sheer is a Registered Trade Mark No. 2296586 All accessories are manufactured under an accredited It is the policy of the company to improve products	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:00 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Re T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered O E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in	Ad, Brislington, Bristol, BS4 5NZ ffice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Trimble, product selector SSPUS

SL