SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


## 86DPBL-B

Sheer Satin Chrome 1 gang 20AX Double Pole Rocker Black/Black


## Item Image







## **Dimensions**



Primary Range			
Plate Finish   Sheer Box Satin Chrome	Primary Range	Sheer	
Black/Black	Insert Type	1 gang 20AX Double Pole Rocker	
EAN13 Barcode 5017503081974  Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm  Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A  Minimum Wall Box Depth 35mm Switched Poles Double  Current Rating 20AX  Voltage 220/250V AC  Maximum Load 20 Amp inductive  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3 x 2.5mm2  Terminal Capacity 2 2 x 4mm2 Multi Strand  Terminal Capacity 3 1 x 6mm2  Earth Terminal Capacity 1 6 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 5 5 x 1.5mm2  Earth Terminal Capacity 5 5 x 1.5mm2  Earth Terminal Capacity 5 1 x 6mm2  Froduct Class 1 Multi be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	Plate Finish	Sheer Box Satin Chrome	
Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = N/A           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         20AX           Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3 x 2.5mm2           Terminal Capacity 2         2 x 4mm2 Multi Strand           Terminal Capacity 3         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only	Insert Colour	Black/Black	
Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = N/A           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         20AX           Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3 x 2.5mm2           Terminal Capacity 2         2 x 4mm2 Multi Strand           Terminal Capacity 3         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only	EAN13 Barcode	5017503081974	
Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         20AX           Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3 x 2.5mm2           Terminal Capacity 2         2 x 4mm2 Multi Strand           Terminal Capacity 3         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only	Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm	
Switched Poles         Double           Current Rating         20AX           Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3 x 2.5mm2           Terminal Capacity 2         2 x 4mm2 Multi Strand           Terminal Capacity 3         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A	
Current Rating         20AX           Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3 x 2.5mm2           Terminal Capacity 2         2 x 4mm2 Multi Strand           Terminal Capacity 3         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only	Minimum Wall Box Depth	35mm	
Voltage         220/250V AC           Maximum Load         20 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3 x 2.5mm2           Terminal Capacity 2         2 x 4mm2 Multi Strand           Terminal Capacity 3         1 x 6mm2           Earth Terminal Capacity 1         6 x 1mm2           Earth Terminal Capacity 2         5 x 1.5mm2           Earth Terminal Capacity 3         3 x 2.5mm2           Earth Terminal Capacity 4         2 x 4mm2 Multi-strand           Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only	Switched Poles	Double	
Maximum Load 20 Amp inductive  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3 x 2.5mm2  Terminal Capacity 2 2 x 4mm2 Multi Strand  Terminal Capacity 3 1 x 6mm2  Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Earth Terminal Capacity 4 5 x 1.5mm2  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	Current Rating	20AX	
Mains Frequency   50Hz     P Rating   IP2XD     Contact Gap Minimum   3mm     Terminal Capacity 1   3 x 2.5mm2     Terminal Capacity 2   2 x 4mm2 Multi Strand     Terminal Capacity 3   1 x 6mm2     Earth Terminal Capacity 1   6 x 1mm2     Earth Terminal Capacity 2   5 x 1.5mm2     Earth Terminal Capacity 3   3 x 2.5mm2     Earth Terminal Capacity 4   2 x 4mm2 Multi-strand     Earth Terminal Capacity 5   1 x 6mm2     Product Class 1   Must be earthed     Ambient Operating Temperature   -5° to +40°C     Recommended Location   Internal Use Only	Voltage	220/250V AC	
P Rating	Maximum Load	20 Amp inductive	
Contact Gap Minimum  Terminal Capacity 1  3 x 2.5mm2  Terminal Capacity 2  2 x 4mm2 Multi Strand  Terminal Capacity 3  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  2 x 4mm2 Multi-strand  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only	Mains Frequency	50Hz	
Terminal Capacity 1 3 x 2.5mm2  Terminal Capacity 2 2 x 4mm2 Multi Strand  Terminal Capacity 3 1 x 6mm2  Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 4 1 x 6mm2  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	IP Rating	IP2XD	
Terminal Capacity 2  2 x 4mm2 Multi Strand  Terminal Capacity 3  1 x 6mm2  Earth Terminal Capacity 1  Earth Terminal Capacity 2  5 x 1.5mm2  Earth Terminal Capacity 3  3 x 2.5mm2  Earth Terminal Capacity 4  2 x 4mm2 Multi-strand  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only	Contact Gap Minimum	3mm	
Terminal Capacity 3  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  I x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only	Terminal Capacity 1	3 x 2.5mm2	
Earth Terminal Capacity 1 6 x 1mm2  Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	Terminal Capacity 2	2 x 4mm2 Multi Strand	
Earth Terminal Capacity 2 5 x 1.5mm2  Earth Terminal Capacity 3 3 x 2.5mm2  Earth Terminal Capacity 4 2 x 4mm2 Multi-strand  Earth Terminal Capacity 5 1 x 6mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	Terminal Capacity 3	1 x 6mm2	
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only	Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 4  Earth Terminal Capacity 5  1 x 6mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only	Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 5         1 x 6mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only	Earth Terminal Capacity 3	3 x 2.5mm2	
Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	Earth Terminal Capacity 5	1 x 6mm2	
Recommended Location Internal Use Only	Product Class 1		
,	Ambient Operating Temperature	-5° to +40°C	
Maximum Installation Altitude 2000m	Recommended Location	Internal Use Only	
	Maximum Installation Altitude	111	
Standard/Approval BS EN 60669-1	Standard/Approval	BS EN 60669-1	
Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586	Patents and Trademarks	Sheer is a Registered Trade Mark No. 2296586	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











Correct as at 17 October 2018 10:00 AM



E&OE

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing

process and are not binding.