SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

86SS2USBULTSC-W

the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of of certain finishes.	86SS2USBULTSC-W Sheer Satin Chrome 2 gang 13A Double Pole Switched Socket with 2 USB Ultra Outlets 2x2.4A Satin Chrome/White			
Primary Range Sheer Insert Type 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) Plate Finish Sheer Soc Satin Chrome Insert Colour Satin Chrome EANT 3 Berocket Commodity Code Sission Chrome EANT 3 Berocket Commodity Code Sission Chrome EANT 3 Berocket Commodity Code Sission Chrome Commodity Code Sission Chrome EANT 3 Berocket EANT 3 Berocket Commodity Code Sission Chrome EANT 3 Berocket EANT 4 Berocket	Item Image	Wiring	Dimensions	
Primary Range Sheer Insert Type 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) Plate Finish Insert Colour Sain Chrome EAN13 Barcocke 5175A4900000 Commodity Code 55353010 Luckins TSI 405887167 Dimensions (Normal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fining Hote Centres 80x Fibring = 120.6mm Grid Fixing = NA Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180250V AC Maximum Load 13 Amp, USB = 2.4A Mans Frequency 500012 PRating 1902 Contact Gag Minimum 7 Terminal Capacity 2 3x 4mm2 Terminal Capacity 2 3x 4mm2 Earth Terminal Capacity 2 3x 4mm2 Earth Terminal Capacity 3 3x 2.5mm2 Earth Terminal Capacity 3 3x 4mm2 Earth Terminal Capacity 3			×	
Pater Type			<u> </u>	
Pater Type				
Insert Type 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) Plate Finish Sheer Box Satin Chrome Insert Colour Satin Chrome Viville EAN13 Barcode 5017504090500 Commodity Code 85363010 Luckins TSI 405887167 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Bax Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz PRating IPZXD Contact Gap Minimum 3mm 3mm 3mm Terminal Capacity 1 3 x Z.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 5 5 mm2 Multi-Strand Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Altitude 18 x 18				
Insert Type 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) Plate Finish Sheer Box Satin Chrome Insert Colour Satin Chrome Viville EAN13 Barcode 5017504090500 Commodity Code 85363010 Luckins TSI 405887167 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Bax Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz PRating IPZXD Contact Gap Minimum 3mm 3mm 3mm Terminal Capacity 1 3 x Z.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 5 5 mm2 Multi-Strand Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Altitude 18 x 18				
Insert Type 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) Plate Finish Sheer Box Satin Chrome Insert Colour Satin Chrome Viville EAN13 Barcode 5017504090500 Commodity Code 85363010 Luckins TSI 405887167 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Bax Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz PRating IPZXD Contact Gap Minimum 3mm 3mm 3mm Terminal Capacity 1 3 x Z.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 5 5 mm2 Multi-Strand Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Altitude 18 x 18				
Insert Type 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) Plate Finish Sheer Box Satin Chrome Insert Colour Satin Chrome Viville EAN13 Barcode 5017504090500 Commodity Code 85363010 Luckins TSI 405887167 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Bax Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz PRating IPZXD Contact Gap Minimum 3mm 3mm 3mm Terminal Capacity 1 3 x Z.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 5 5 mm2 Multi-Strand Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Altitude 18 x 18				
Insert Type 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) Plate Finish Sheer Box Satin Chrome Insert Colour Satin Chrome Viville EAN13 Barcode 5017504090500 Commodity Code 85363010 Luckins TSI 405887167 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Bax Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz PRating IPZXD Contact Gap Minimum 3mm 3mm 3mm Terminal Capacity 1 3 x Z.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 5 5 mm2 Multi-Strand Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Altitude 18 x 18				
Insert Type 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) Plate Finish Sheer Box Satin Chrome Insert Colour Satin Chrome Viville EAN13 Barcode 5017504090500 Commodity Code 85363010 Luckins TSI 405887167 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Bax Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz PRating IPZXD Contact Gap Minimum 3mm 3mm 3mm Terminal Capacity 1 3 x Z.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 5 5 mm2 Multi-Strand Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Altitude 18 x 18				
Insert Type 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) Plate Finish Sheer Box Satin Chrome Insert Colour Satin Chrome Viville EAN13 Barcode 5017504090500 Commodity Code 85363010 Luckins TSI 405887167 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Bax Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz PRating IPZXD Contact Gap Minimum 3mm 3mm 3mm Terminal Capacity 1 3 x Z.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 5 5 mm2 Multi-Strand Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Altitude 18 x 18				
Insert Type 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) Plate Finish Sheer Box Satin Chrome Insert Colour Satin Chrome Viville EAN13 Barcode 5017504090500 Commodity Code 85363010 Luckins TSI 405887167 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Bax Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz PRating IPZXD Contact Gap Minimum 3mm 3mm 3mm Terminal Capacity 1 3 x Z.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 3 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 5 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 4mm2 Earth Terminal Capacity 3 8 x 5 5 mm2 Multi-Strand Recommended Location Internal Use Only Maximum Installation Altitude 2000m Maximum Installation Altitude 2000m Altitude 18 x 18				
Plate Finish Sheer Box Satin Chrome	Primary Range	Sheer		
Insert Colour	Insert Type	2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total)		
EAN13 Barcode	Plate Finish	Sheer Box Satin Chrome		
Commodity Code	Insert Colour	Satin Chrome/White		
Luckins TSI 405687167 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 150.2500 AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50.60Hz PRating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x 2.5mm2 Terminal Capacity 1 3x 2.5mm2 Terminal Capacity 2 3x 4mm2 Earth Terminal Capacity 2 3x 4mm2 Earth Terminal Capacity 2 3x 4mm2 Earth Terminal Capacity 3 2x 6mm2 Multi-Strand Product Class 1 Must be earthed Ambient Operating Temperature 15°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363 + BS 5733 + EN 60950-1 Battle Tardemanks All proxices laided conform to current British or European standard and the product information is correct at the time of gioing to press. Due to manufacturing processes are not binding. Due to manufacturing processes we cannot guarantee an exact occlour match and shadings of certain finense.	EAN13 Barcode	5017504090500		
Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load Mains Frequency 50/60Hz IP Rating IP2XD Contact Gap Minimum 3mm Ferminal Capacity 1 3 x 2.5mm2 Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Farth Terminal Capacity 3 2 x 6mm2 Multi-strand Forduct Class 1 Must be earthed Ambient Operating Temperature 1-15°C to 1-40°C Recommended Location Maximum Installation Altitude 2000m Standard/Approval Bas 1363 + BS 5733 + EN 60950-1 Billustrations and diagrams are reproduction and printing current and shadings of or certain firehises.	Commodity Code	85363010		
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 Product Class 1 Must be earthed Ambient Operating Temperature -15°C to +40°C Recommended Location Maximum Installation Altitude 2000m Standard/Approval BS 1363 + BS 5733 + EN 60950-1 Alt products Its de not only indirection and printing process and and diagrams are reproduced within the limitations of reproduction and printing process and a report broises. EXD Correct as the time of going to press. EXD Correct as the time of going to press. Due to manufacturing processes we cannot guarantee an exact colour maket and stadings of of certain finishes.	Luckins TSI	405687167		
Minimum Wall Box Depth Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency IP Rating IP2XD Contact Gap Minimum Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand arth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Ambient Operating Temperature -15°C to +40°C Maximum Installation Altitude 2000m Maximum Installation Altitude All products listed conform to current British or European standard and the product information is correct at the time of gingit to press. All products listed conform to current British or European standard and the product information is correct at the time of gingit to press. All products listed conform to current British or European standard and the product information is correct at the time of gingit to press. All products listed conform to current British or European standard and the product information is correct at the time of gingit to press. All products listed conform to current British or European standard and the product information is correct at the time of gingit to press. All products listed conform to current British or European standard and the product information is correct at the time of gingit to press. All products listed conform to current British or European standard and the product information is correct at the time of gingit to press. All products listed conform to current British or European standard and the product information is correct at the time of gingit to press. All products listed conform to current British or European standard and and error to briting. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of ofertal finishes.	Dimensions (Nominal)	Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm		
Switched Poles Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz IP Rating IP2XD Contact Gap Minimum Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 3 Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Must be earthed Ambient Operating Temperature 1-15°C to +40°C Recommended Location Maximum Installation Altitude 2000m Standard/Approval Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of ging to priess. All products listed conform to current British or European standard and the product information is correct at the time of ging to priess. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of ofertain finishes. EXOC.	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A		
Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Product Class 1 Must be earthed Ambient Operating Temperature 1.15°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Bs 1363 + BS 5733 + EN 60950-1 Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is current at the time of going to press. All products listed conform to current British or European standard and the product information is current at the time of going to press. All products listed conform to current British or European standard and the product information is current at the time of going to press. All products listed conform to current British or European standard and the product information is current at the time of going to press. All products listed conform to current British or European standard and the product information is current at the time of going to press. All products listed conform to current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or European standard and the product information is current British or Green timinities and current British or European standard and the product infor	Minimum Wall Box Depth	35mm		
Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x 2.5mm2 Terminal Capacity 2 3x 4mm2 Terminal Capacity 3 2x 6mm2 Multi-Strand Earth Terminal Capacity 1 3x 2.5mm2 Earth Terminal Capacity 2 3x 4mm2 Earth Terminal Capacity 2 3x 4mm2 Earth Terminal Capacity 2 3x 4mm2 Earth Terminal Capacity 3 2 2x 6mm2 Multi-Strand Earth Terminal Capacity 3 3x 4mm2 Earth Terminal Capacity 3 2x 6mm2 Multi-strand Product Class 1 Must be earthed Ambient Operating Temperature -15°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Bs 1363 + BS 5733 + EN 60950-1 Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the file of gloing to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as a 03 July 2019 07:23 AM E&OF	Switched Poles	Double		
Maximum Load 13 Amp, USB = 2.4A Mains Frequency 50/60Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Product Class 1 Ambient Operating Temperature -15°C to +40°C Recommended Location Maximum Installation Altitude 2000m Standard/Approval Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. But the time of going to press. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of cof certain frilishes. Correct at st 03 July 2019 07-23 AM E&O	Current Rating	13 Amp, USB = 2.4A		
Mains Frequency Pating Pa	Voltage			
IP2XD	Maximum Load	13 Amp, USB = 2.4A		
Contact Gap Minimum Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Product Class 1 Ambient Operating Temperature Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Best Niso 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of or cereating finishes.	Mains Frequency			
Terminal Capacity 1 3 x 2.5mm2 Terminal Capacity 2 3 x 4mm2 Terminal Capacity 3 2 x 6mm2 Multi-Strand Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Product Class 1 Must be earthed Ambient Operating Temperature -15°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363 + BS 5733 + EN 60950-1 Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Billustrations and diagrams are reproduced within the limitations of reproduction and printing processes and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	IP Rating			
Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth	· · · · · · · · · · · · · · · · · · ·			
Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Product Class 1 Ambient Operating Temperature -15°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. But to manufacturing processes we cannot the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.				
Earth Terminal Capacity 1 3 x 2.5mm2 Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Product Class 1 Must be earthed Ambient Operating Temperature -15°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363 + BS 5733 + EN 60950-1 Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BIllustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 03 July 2019 07:23 AM E&OE				
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Product Class 1 Ambient Operating Temperature -15°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363 + BS 5733 + EN 60950-1 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Blilustrations and diagrams are reproduced within the limitations of reproduction and printing processes are necessarily and the product information guarantee an exact colour match and shadings of process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. Correct as at 03 July 2019 07:23 AM E&OE				
Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Product Class 1 Must be earthed Ambient Operating Temperature -15°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Bs 1363 + Bs 5733 + EN 60950-1 Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of certain finishes.				
Product Class 1 Ambient Operating Temperature -15°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363 + BS 5733 + EN 60950-1 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BIllustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Must be earthed -15°C to +40°C Recommended Location Internal Use Only BS 1363 + BS 5733 + EN 60950-1 Sheer is a Registered Trade Mark No. 2296586 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 03 July 2019 07:23 AM E&OE of certain finishes.	. ,			
Ambient Operating Temperature -15°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363 + BS 5733 + EN 60950-1 Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.				
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363 + BS 5733 + EN 60950-1 Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.				
Maximum Installation Altitude 2000m Standard/Approval Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. BS 1363 + BS 5733 + EN 60950-1 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 03 July 2019 07:23 AM E&OE				
Standard/Approval Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. Blustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. BS 1363 + BS 5733 + EN 60950-1 Sheer is a Registered Trade Mark No. 2296586 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 03 July 2019 07:23 AM E&OE of certain finishes.				
Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 03 July 2019 07:23 AM E&OE				
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 03 July 2019 07:23 AM E&OE of certain finishes.				
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 03 July 2019 07:23 AM E&OE			It is the policy of the second in	
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of of certain finishes.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ	the limitations of reproduction and printing process and are not binding.	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 03 July 2019 07:23 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









