## Hamilto

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

Sheer Bright Chrome 2 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers Bright Chrome Item Image Wiring Dimensions Hamilton SHEER 2X2V ding Edge Push On-Off Rotary /ay Switching Dimmer 60.3 Primary Range Sheer Insert Type 2 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers Plate Finish Sheer Box Bright Chrome Insert Colour Bright Chrome EAN13 Barcode 5017503099122 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm 216 GR Weight **Fixing Hole Centres** Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 200VA (low voltage) per gang Switched Poles Single Current Rating 0.8 Amp Voltage 220/250V AC Maximum Load 200VA per gang (low voltage) Min Load 25VA Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None **Terminal Capacity 1** 2 x 1mm2 **Terminal Capacity 2** 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When Additional Notes dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE: It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load. Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme correct at the time of going to press Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 17 October 2018 10:01 AM guarantee an exact colour match and shadings of the limitations of reproduction and printing E&OE process and are not binding. of certain finishes. R Hamilton & Co Ltd. Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ **SECA** Listed in 🔅 Trimble T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 LUCKINS

872X2V

872X2V - Sheer Bright Chrome 2 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers Bright Chrome

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio