SL

making connections beautifully

	Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio		
Primary Range GRID-IT Insert Type 9 Gang Grid Fix Aperture Plate with Grid Plate Finish Shere GRID-IT Bright Chrome Insert Colour No Insert Colour No Insert Colour No Insert Colour RAN13 Barcode So51164879099 Dimensions Switched Poles No Ninimum Wall Box Depth Switched Poles No NA Per Inserts Switched Poles NA IP Rating NA IP Rating NA Earth Terminal Capacity 1 11mm2 Product Glass 1 Face plate must be earthed Internal Capacity 1 11mm2 Product Class 1 Face plate must be earthed Racommended Location Internal Lacoscories are manufactured under an accredited Bas Fixing and Internal Lacoscories are manufactured under an accredited Bas Fixing and Internal Lacoscories are manufactured under an accredited Bas Fixing on Internal Lacoscories are manufactured under an accredited Bas Fixing on Internal Lacoscories are manufactured under an accredited Bas Fixing on Internal Lacoscories are manufactured under an accredited Bas Fixing on Internal Lacoscories are manufactured under an accredited Bas Fixing Dubo Internal Spixen. Part Internal Lacoscories are manufactured under an accredited Bas Fixing Dubo Internal Spixen. Purport is at 15 October 2015 Quality Management System. Current as at 15 October 2015 Spixel Spixen.		<u>879GP</u>	
Primary Range GRID-IT Insert Type 9 Gang Grid Fix Aperture Plate with Grid Plate Finish Shere GRID-IT Bright Chrome Insert Colour No Insert Colour No Insert Colour No Insert Colour RAN13 Barcode So51164879099 Dimensions Switched Poles No Ninimum Wall Box Depth Switched Poles No NA Per Inserts Switched Poles NA IP Rating NA IP Rating NA Earth Terminal Capacity 1 11mm2 Product Glass 1 Face plate must be earthed Internal Capacity 1 11mm2 Product Class 1 Face plate must be earthed Racommended Location Internal Lacoscories are manufactured under an accredited Bas Fixing and Internal Lacoscories are manufactured under an accredited Bas Fixing and Internal Lacoscories are manufactured under an accredited Bas Fixing on Internal Lacoscories are manufactured under an accredited Bas Fixing on Internal Lacoscories are manufactured under an accredited Bas Fixing on Internal Lacoscories are manufactured under an accredited Bas Fixing on Internal Lacoscories are manufactured under an accredited Bas Fixing Dubo Internal Spixen. Part Internal Lacoscories are manufactured under an accredited Bas Fixing Dubo Internal Spixen. Purport is at 15 October 2015 Quality Management System. Current as at 15 October 2015 Spixel Spixen.	Sheer Grid-l	T Bright Chrome 9 Gang Grid Fix Aperture P	late with Grid
Primary Range GRID-IT Insert Type 9 Gang Grid Fix Aperture Plate with Grid Plate Finish Sheer GRID-IT Bright Chrome Insert Colour No Insert Colour EAN13 Barcode 5051164879099 Dimensions (Nominal) 150x210: Height = 210mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres 90x Fixing = 120.8mm x 3 Grid Fixing = 106.5mm x3 Minimum Wall Box Depth As Per Inserts Switched Poles N/A IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 11mm2 Froduct Class 1 Face plate must be earthed Recommended Location Internal Use Only Maximum Installation Altitude 2000m Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All products listed conform to current British or European standard and the product information is See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All accessories are manufactured under an accredied SE NI ISO 9001 : 2015 SO Quity Management System. It is the policy of the company to improve products so part of our development programms. Product of the third of playing to press. Plates must be Earthed via the Earth Tag. All accessories are manufactured under an accredied SE NI ISO 9001 : 2015 SO Quity Management System. It is the policy of the company to improve products so part of our development programms. Plates must be Earthed and development programms. Plates must be earthed for control at the lime of playing to press. Plates must be Earthed via the Earth Tag. All accessories are manufactured under an accredied SE NI ISO 9001 : 2015 Quity Management System. It is the policy of price can be part of our formation and difference with playing and dimensions without playing repression and difference with playing and dimensions without playing and dimensions without playing repression. See CRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All accessories are manufactured under an accredied SE NI ISO 900 1 : 2	Shoot Sha t	Bright Children & Carry Charlin, Apoltare	Tato Will Grid
Primary Range GRID-IT Insert Type 9 Gang Grid Fix Aperture Plate with Grid Plate Finish Sheer GRID-IT Bright Chrome Insert Colour No Insert Colour EAN13 Barcode 5051164879099 Dimensions (Nominal) 150x210: Height = 210mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm x 3 Grid Fixing = 106.5mm x3 Minimum Wall Box Depth As Per Inserts Switched Poles N/A IP Rating N/A Contact Gap Minimum N/A	Item Image	Wiring	Dimensions
Insert Type 9 Gang Grid Fix Aperture Plate with Grid Plate Finish Sheer GRID-IT Bright Chrome Insert Colour No Insert Colour EAM13 Barcode 5051164879099 Dimensions (Nominal) 150x210: Height = 210mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm x 3 Grid Fixing = 106.5mm x 3 Minimum Wall Box Depth As Per Inserts Switched Poles N/A IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 11mm2 Product Class 1 Face plate must be earthed Recommended Location Internal Use Only Maximum Installation Altitude 2000m Additional Notes See GRID-IT for a full range of inserts. Plates must be Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Be No Fixing Plate with Grid Sheer GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Be No 9001: 2015 Quality Management System. Due to manufacturing processes we cannot reserve the right to alter designs and diagrams are reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 A EAO			SHEER 9GP Large plate with 9 x GRID-IT cutout
Plate Finish Sheer GRID-IT Bright Chrome Insert Colour No Insert Colour FAN13 Barcode 5051164879099 Dimensions (Nominal) 150x210: Height = 210mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm x 3 Grid Fixing = 106.5mm x3 Minimum Wall Box Depth As Per Inserts Switched Poles IVA Contact Gap Minimum N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 Inmm2 Frace plate must be earthed Recommended Location Internal Use Only Maximum Installation Altitude Additional Notes All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9011 : 2015 Quality Management System. BEN ISO 9011 : 2015 Quality Management System. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of SEA Microal SEA Mi			
Insert Colour EAN13 Barcode 5051164879099 Dimensions (Nominal) 150x210: Height = 210mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm x 3 Grid Fixing = 106.5mm x3 Minimum Wall Box Depth As Per Inserts Switched Poles N/A IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 11mm2 Product Class 1 Recommended Location Maximum Installation Altitude Additional Notes All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 A E&O			
EAN13 Barcode Dimensions (Nominal) 150x210: Height = 210mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm x 3 Grid Fixing = 106.5mm x3 Minimum Wall Box Depth As Per Inserts Switched Poles N/A IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 11mm2 Product Class 1 Recommended Location Internal Use Only Maximum Installation Altitude Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 A EAO			
Dimensions (Nominal) 150x210: Height = 210mm Width = 146.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm x 3 Grid Fixing = 106.5mm x3 Minimum Wall Box Depth As Per Inserts Switched Poles N/A IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 Product Class 1 Recommended Location Internal Use Only Maximum Installation Altitude Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 All E&A EAN EAR			
Fixing Hole Centres Box Fixing = 120.6mm x 3 Grid Fixing = 106.5mm x3 Minimum Wall Box Depth As Per Inserts W/A IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 Internal Capacity 1 Product Class 1 Recommended Location Internal Use Only Maximum Installation Altitude Additional Notes See GRID-IT for a full range of inserts. Plates must be Earth et as part of our development programme. Currect at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. But is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 All E&O			
Minimum Wall Box Depth As Per Inserts Switched Poles N/A IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 Imm2 Product Class 1 Recommended Location Recommended Location Internal Use Only Maximum Installation Altitude Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 All E&O			
Switched Poles N/A IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 11mm2 Product Class 1 Face plate must be earthed Recommended Location Internal Use Only Maximum Installation Altitude 2000m Additional Notes See GRID-IT for a full range of inserts. Plates must be Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 All E&O			
IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 11mm2 Product Class 1 Face plate must be earthed Recommended Location Internal Use Only Maximum Installation Altitude 2000m Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 All E&O			
Contact Gap Minimum N/A Earth Terminal Capacity 1 Product Class 1 Recommended Location Internal Use Only Maximum Installation Altitude Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 All E&O			
Earth Terminal Capacity 1 Product Class 1 Recommended Location Internal Use Only Maximum Installation Altitude Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 All E&O			
Product Class 1 Face plate must be earthed Recommended Location Internal Use Only Maximum Installation Altitude 2000m Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 All E&O	·	11mm2	
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 All E&O			
Maximum Installation Altitude 2000m See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BILIUSTRATIONS and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 Al E&O		-	
Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BILIUSTRATIONS and diagrams are reproduced within the limitations of reproduction and printing BOULD TO A full range of inserts. Plates must be Earthed via the Earth Tag. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 15 October 2018 09:53 All E&O			
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E&O E&O		See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag.	
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&O	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ	the limitations of reproduction and printing process and are not binding.	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:53 AM E&OE

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









