making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

87C1XI FDITR100

the limitations of reproduction and printing guarantee an exact colour match and shadings of E&O	87C1XLEDITB100 Sheer CFX Bright Chrome 1g 100W LED 2 Way Push On/Off Rotary Dimmer Bright Chrome			
Primary Range Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with 884662-2006. Insent Type 1 gaing 100W LED Trailing/Loading Edge Point On/Off Rotary 2 Way Switching Dimmur Plate Finish Sheer CFX Bright Chrome Insent Colour Brig	Item Image	Wiring	Dimensions	
Insert Type			1XLEDITB LEDITB100 2 Way Dimmer	
Plate Finish Insert Colour Bright Chrome Shart Crown Bright Chrome SAN13 Barcode John Sold Sold Sold Sold Sold Sold Sold Sold				
Insert Colour Bright Chrome EAN13 Barcode 501750480822 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-100W (10 LED Lamps MAX) Switched Poles Single Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) Mains Frequency 50Hz IP Rating IPXD Terminal Capacity 1 2X1mm² Terminal Capacity 1 2X1mm² Earth Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 3 1X4.5mm² Earth Terminal Capacity 4 5X1.5mm² Earth Terminal Capacity 5 1X6mm² Earth Terminal Capacity 5 1X6mm² Earth Terminal Capacity 5 1X6mm² Earth Terminal Capacity 6 1X6mm² Earth Terminal Capacity 6 1X6mm² Earth Terminal Capacity 6 1X6mm² Earth Terminal Capacity 7 1X6mm² Earth Terminal Capacity 8 1X6mm² Earth Terminal Capacity 9 1X6mm² Earth Terminal Capacity 5 1X6mm² Froduct Class 1 Face plate muct be earthed Ambient Operating Temperature 5°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 All products listed conform to current British or European standard and the product reformation is correct at the time of laying brigon. All products listed conform to current British or European standard and the product reformation is correct at the time of laying brigon. BE N 150 9001 : 2015 Caulanty Management System. Bustratore and diagrams are reproduced within the limitations of reproduction and printing of gusarines are are amendactured under an accrediate as a part of our development potention. Bustratore and diagrams are reproduced within the limitations of reproduced within the limitations of reproduction and printing of gusarines are accrediated and sheddings of EXC				
EAN13 Barcode 5017504080822 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-100W (10 LED Lamps MAX) Switched Poles Single Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1.5mm² Ferminal Capacity 1 2X1.5mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm² Earth Terminal Capacity 5 1X6mm² Earth Terminal Capacity 6 1X6mm² Earth Terminal Capacity 7 1X6mm² Earth Terminal Capacity 8 1X6mm² Earth Terminal Capacity 9 1X6mm² Ear				
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-100W (10 LED Lamps MAX) Switched Poles Single Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) Mains Frequency FP Rating P2XD Ferminal Capacity 1 2X1mm² Terminal Capacity 1 2x1.5mm² Earth Terminal Capacity 2 3x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 3 Terminal Capacity 4 1x4mm² Multi-Strand Earth Terminal Capacity 5 Tarbinal Capacity 5 Tarbinal Capacity 6 Ta				
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Wattage 5-100W (10 LED Lamps MAX) Switched Poles Single Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) Mains Frequency 19 Rating 19 PZXD Terminal Capacity 1 Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 5 Froduct Class 1 Face plate much be earthed Ambient Operating Temperature -5°C to +40°C Recommended Location Maximum Installation Altitude 2000m Additional Notes Trailing Edge & Leading Edge Dimmer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products lated conform to current British or European standard and he product information is correct at the time of going to press. But the minimum of production and her product information is correct at the time of going to press.				
Minimum Wall Box Depth 35mm Watage 5-100W (10 LED Lamps MAX) Switched Poles Single Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) Mains Frequency 50Hz IP Rating IP ZXD Terminal Capacity 1 2X1mm² Terminal Capacity 1 2X1mm² Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm² Earth Terminal Capacity 6 1X6mm² Face plate muct be earthed Ambient Operating Temperature 5°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer Patents and Trademarks CPX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sher CPX is a Registered Trade Mark No 2398667 Trade Mark No. 296586 Sher CPX is a Registered Trade Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a derivative funder an accredited Sher No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a Registered Toale Mark No. 296586 Sher CPX is a derivative funder an accredited Sher No. 296586 Sher CPX is a derivative				
S-100W (10 LED Lamps MAX) Switched Poles Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) Mains Frequency Fortill Rating 1P2XD Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity				
Switched Poles Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) Mains Frequency 5-100W (10 LED Lamps MAX) 5-100W (10 LED Lamps MAX) Mains Frequency 5-100W (10 LED Lamps MAX) 5-100W (10 Lamps MAX				
Current Rating 0.4A Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm² Forduct Class 1 Face plate muct be earthed Ambient Operating Temperature .5°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited as a part of our development programme. Therefore, we reserve the right to after designs and dimensions without prior notice. Bue to manufacturing processes we cannot Correct as at 17 October 2018 1.042 At EAU Correct as at 17 October 2018 1.042 At EAU Correct as at 17 October 2018 1.042 At EAU Correct as at 17 October 2018 1.042 At EAU Correct as at 17 October 2018 1.042 At EAU Correct as at 17 October 2018 1.042 At EAU Correct as at 17 Octob				
Voltage 230V-240V Maximum Load 5-100W (10 LED Lamps MAX) Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 22/1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 3 1X6mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm² Product Class 1 5 Face plate muct be earthed Ambient Operating Temperature 5-5°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No, 2298586 Sheer CFX is a Registered Trade Mark No 2398667 Trade Mark No, 2296586 Sheer CFX is a Registered Trade Mark No 2398667 Trade Mark No, 2296586 Sheer CFX is a Registered Trade Mark No 2398667 Trade Mark No, 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot Correct as at 17 October 2018 10.42 All guarantee an exact colour match and shadings of Correct as at 17 October 2018 10.42 All guarantee an exact colour match and shadings of Correct as at 17 October 2018 10.42 All guarantee an exact colour match and shadings of Correct as at 17 October 2018 10.42 All guarantee an exact colour match and shadings of Correct as at 17 October 2018 10.42 All guarantee an exact colour match and shadings of Correct as at 17 October 2018 10.42 All guarantee an exact colour match and shadings of Correct as at 17 October 2018 10.42 All guarantee an exact colour match and shadings of Corr				
Maximum Load 5-100W (10 LED Lamps MAX) Mains Frequency 50Hz IP Rating IP ZXD Terminal Capacity 1 2X11mm² Earth Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 IX4mm² Multi-Strand Earth Terminal Capacity 5 IX6mm² Froduct Class 1 Ambient Operating Temperature -5°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes Patents and Trademarks All products listed conform to current British or European standard and the product information is Correct at the time of going to press. All products listed conform to current British or European standard and the product information is Correct at the time of going to press. Be EN SO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and diagrams are reproducted within the limitations of Peroproduction and printing Due to manufacturing processes we cannot the product of ord revelopment programme. Therefore, we reserve the right to alter designs and dimensions without prior motice. EXCOMPANIENT OF TARGET OF TARGE	-			
Mains Frequency Pating IP2XD	-			
IP Rating				
Terminal Capacity 1 Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bullustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 10:42 A EACH CAPPACIAN CORD CORD CORD CORD CORD CORD CORD CORD				
Terminal Capacity 2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Ca	-			
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm² Product Class 1 Face plate muct be earthed Ambient Operating Temperature -5°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes Patents and Trademarks Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 10:42 All Search Colour match and shadings of				
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Face plate muct be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduction and printing Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of EXCOMPANDA AX1.5mm² 1X4mm² Multi-Strand 1X4mm² Multi-Strand 1X4mm² Multi-Strand 1X4mm² Multi-Strand 1X4mm² Multi-Strand 1X6mm² Face plate muct be earthed 25°C to +40°C Recommended Location Internal Use Only BS EN 60669-2-1 Trailing Edge & Leading Edge Dimmer CFX is a Registered Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of EAO				
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS EN 60669-2-1 Additional Notes Patents and Trademarks CFX is a Registered Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing BX2.5mm² 1X4mm² Multi-Strand 1X4mm² Multi-Strand 1X6mm² Pace plate muct be earthed -5°C to +40°C Recommended Location Internal Use Only BS EN 60669-2-1 Trailing Edge Dimmer CFX is a Registered Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All accessories are manufactured under an accredited BS EN ISO 3001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 10:42 All EACH Correct and Pack Correct as at 17 October 2018 10:42 All EACH Correct and Pack Correct as at 17 October 2018 10:42 All EACH Correct and Pack Correct as at 17 October 2018 10:42 All EACH Correct and Pack Correct as at 17 October 2018 10:42 All EACH Correct and Pack Correct as at 17 October 2018 10:42 All EACH Correct and Pack Correct as at 17 October 2018 10:42 All EACH Correct and Pack Correct as at 17 October 2018 10:42 All EACH Correct and Pack Correct as at 17 October 2018 10:42 All EACH Correct and Pack Correct as at 17 October 2018 10:42 All EACH Correct and Pack C				
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature -5°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. But is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot the limitations of reproduction and printing guarantee an exact colour match and shadings of E&O				
Earth Terminal Capacity 5 Product Class 1 Face plate muct be earthed Ambient Operating Temperature -5°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Bllustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 10.42 All scannot guarantee an exact colour match and shadings of				
Product Class 1 Ambient Operating Temperature -5°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 10:42 All guarantee an exact colour match and shadings of				
Ambient Operating Temperature -5°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 10:42 All E&O				
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Correct as at 17 October 2018 10:42 A E&O		·		
Maximum Installation Altitude 2000m Standard/Approval Additional Notes Trailing Edge & Leading Edge Dimmer Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 10:42 All E&O				
Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 10:42 All E&O		·		
Additional Notes Trailing Edge & Leading Edge Dimmer CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of Trailing Edge & Leading Edge Dimmer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of		111		
Patents and Trademarks CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 17 October 2018 10:42 All E&O				
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 10:42 Al E&O		CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586		
the limitations of reproduction and printing guarantee an exact colour match and shadings of E&O	European standard and the product information is	All accessories are manufactured under an accredited	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs	
process and are not binding. of certain finishes.			Correct as at 17 October 2018 10:42 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1749 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84











