## Hamilton

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 87CR222BC-B Sheer CFX Bright Chrome 2 gang 20AX 2 Way Rocker Bright Chrome/Black Item Image Wiring Dimensions Hamilton R222 2 Way Rocker 86.0 Primary Range Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006. Insert Type 2 gang 20AX 2 Way Rocker Plate Finish Sheer CFX Bright Chrome Insert Colour Bright Chrome/Black EAN13 Barcode 5017504046378 Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single 20AX Current Rating 220/250V AC Voltage 20 Amp inductive Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm **Terminal Capacity 1** 5 x 1mm2 **Terminal Capacity 2** 4 x 1.5mm2 **Terminal Capacity 3** 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Internal Use Only **Recommended Location** Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Patents and Trademarks Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme. Therefore, we reserve the right to alter designs correct at the time of going to press and dimensions without prior notice. Correct as at 17 October 2018 10:42 AM Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of E&OE process and are not binding of certain finishes R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimb SECA +44 (0)1747 860088 F: +44 (0)1179 710414 info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84 LUCKINS E: info@

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio