making connections beautifully

SL

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

87CSS2USBULTBC-W

| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | Wiring | Dimensions |
|---|--|--|
| Primary Range Sheer CFX - Designed to Insert Type Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chrom Insert Colour EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | Ü | × |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | × |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Insert Type 2 gang 13A Double Pole Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Plate Finish Sheer CFX Bright Chron Insert Colour Bright Chrome/White EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0m Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006. | |
| Insert Colour | 2 gang 13A Double Pole Switched Socket with 2 USB Outlets 2x2.4A (4.8A Total) | |
| EAN13 Barcode 5017504090524 Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0m Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | Sheer CFX Bright Chrome | |
| Commodity Code 85363010 Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0m Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | Bright Chrome/White | |
| Luckins TSI 405687183 Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Dimensions (Nominal) Double: Height = 86.0n Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Fixing Hole Centres Box Fixing = 120.6mm Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket | |
| Switched Poles Double Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | Box Fixing = 120.6mm Grid Fixing = CFX Clips | |
| Current Rating 13 Amp, USB = 2.4A Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | 35mm | |
| Voltage 180/250V AC Maximum Load 13 Amp, USB = 2.4A | | |
| Maximum Load 13 Amp, USB = 2.4A | 13 Amp, USB = 2.4A | |
| | | |
| Mains Fraguency | | |
| Mains Frequency 30/00112 | 50/60Hz | |
| IP Rating IP2XD | | |
| Contact Gap Minimum 3mm | 3mm | |
| Terminal Capacity 1 3 x 2.5mm2 | | |
| Terminal Capacity 2 3 x 4mm2 | 3 x 4mm2 | |
| Terminal Capacity 3 2 x 6mm2 Multi-Strand | | |
| Earth Terminal Capacity 1 3 x 2.5mm2 | | |
| Earth Terminal Capacity 2 3 x 4mm2 | | |
| Earth Terminal Capacity 3 2 x 6mm2 Multi-strand | | |
| Product Class 1 Must be earthed | | |
| Ambient Operating Temperature -15°C to +40°C | | |
| Recommended Location Internal Use Only | | |
| Maximum Installation Altitude 2000m | | |
| | BS 1363 + BS 5733 + EN 60950-1 | |
| Sheer CFX is a Register | CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 | |
| | nanufactured under an accredited 115 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within Due to manufa the limitations of reproduction and printing guarantee an examprocess and are not binding. of | | Correct as at 03 July 2019 07:23 AM E&OE |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84











