SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## 87D26126W

Sheer Floor Bright Chrome 2 gang 10/16A 220/250V AC German Unswitched Socket White

| Item Image  | Wiring  | Dimensions   |
|---|---|--|
|   | Note: This socket in Non Polarised  | Henilton SHEER FLOOR Z8126 Unswitched German Socket    Solid   |
| Primary Range   | Sheer Floor Sockets   |  |
| Insert Type   | 2 gang 10/16A 220/250V AC German Unswitched Socket  |  |
| Plate Finish  | Sheer Floor Box Bright Chrome   |  |
| Insert Colour   | White   |  |
| EAN13 Barcode   | 5017504034993   |  |
| Dimensions (Nominal)  | Double: Height = 93mm Width = 145mm Depth = 3.0mm (6.5mm Hinged Cover)  |  |
| Fixing Hole Centres   | Box Fixing = 120.6mm Grid Fixing = N/A  |  |
| Minimum Wall Box Depth  | 47mm  |  |
| Switched Poles  | None  |  |
| Current Rating  | 10/16 Amp   |  |
| Voltage   | 220/250V AC   |  |
| Maximum Load  | 16 Amp  |  |
| Mains Frequency   | 50Hz  |  |
| IP Rating   | IP2XD   |  |
| Contact Gap Minimum   | None  |  |
| Terminal Capacity 1   | 3 x 2.5mm2  |  |
| Terminal Capacity 2   | 3 x4mm2   |  |
| Terminal Capacity 3   | 2 x 6mm2 Multi-Strand   |  |
| Terminal Capacity 4   | 1 x 10mm2   |  |
| Product Class 1   | Face plate must be earthed  |  |
| Ambient Operating Temperature   | -5° to +40°C  |  |
| Recommended Location  | Internal Use Only   |  |
| Maximum Installation Altitude   | 2000m   |  |
| Standard/Approval   | BS EN ISO 5733 IEC60884-1   |  |
| Additional Notes  | Shuttered:Yes   |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.         | It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 11:27 AM E&OE  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)179710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84









