SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

87DJ45W

Sheer Floor Bright Chrome 1 gang RJ45 CAT 5E Outlet - Unshielded White

Item Image	Wiring	Dimensions
	RAIS CATSe Rear View RAIS CATSe and CATS Wiring Colour Codes Codes Codes RAIS CATSe and CATS Wiring Colour Codes RAIS CATSe Rear View RAIS CATSe and CATS Wiring Codes Codes RAIS CATSe Rear View RAIS CATSe and CATS Wiring Codes Codes RAIS CATSe and CATS Wiring Codes Codes RAIS CATSe Rear View RAIS CATSe and CATS Wiring Codes Codes RAIS CATSe Rear View RAIS CATSe and CATS Wiring Codes Codes RAIS CATSe Rear View RAIS CATSe and CATS Wiring Codes Codes RAIS CATSe Rear View RAIS CATSe and CATS Wiring Codes Codes RAIS CATSe Rear View RAIS CATSe and CATS Wiring Codes Codes RAIS CATSe Codes RAIS CATSE AND CODE CODES RAIS CATSE AND CODES RAIS CATSE AND CODE CODE CODES RAIS CATSE AND CODE CODES RAIS CATSE AND CODE CODE CODE CODE CODE RAIS CATSE AND CODE CODE CODE CODE CODE CODE CODE RAIS CATSE AND CODE CODE CODE CODE CODE CODE CODE COD	Hemilton SHEER FLOOR 145 1 gang RJ45-CAT SE Outlet Unshielded 8 wire Bottom Plats 155 155 155 155 155 155 155 155 155 15
Primary Range	Sheer Floor Sockets	
Insert Type	1 gang RJ45 CAT 5E Outlet - Unshielded	
Plate Finish	Sheer Floor Box Bright Chrome	
Insert Colour	White	
EAN13 Barcode	5017504035051	
Dimensions (Nominal)	Single: Height = 93.5mm Width = 85.5mm Depth = 3.0mm (6.5mm Hinged Cover)	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
EuroFix Additional Notes	Can be used in both EIA 568A and EIA 568B wiriing schedules	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 11:27 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









